




Datasheet

R13-060-MD-PF-L12A

Metal Faced Access Panel - Picture Frame



Walls Only



No Airtight Rating



No Acoustic Rating



1 Hour Fire Rating



Picture Frame

Description

This panel is designed to fit into a structural membrane of a joint-less plasterboard ceiling or wall system. It is manufactured with a 25mm wide picture frame. The panel has a Metal faced door. The panels door leaf is locked in place via a 3 Point Locking System as standard other lock options are available upon request. The Panel is Powder Coated RAL 9010 30% Gloss. Other colours available upon request.

Tests

The Panel is 1 Hour Fire Rated for integrity up to 2000x600mm in a wall application tested in accordance with BS EN 1634-1: 2014.

The Panel is Non acoustic rated.

The Panel is not Air Pressure tested.

The Panel is not Smoke tested.

Seals

Intumescent Seals **YES** Draught Seals **NO** Smoke Seals **NO** Air Seals **NO**

Composition & Manufacture

The R13-060-MD-PF-L12A is manufactured from Zintec Steel with a 0.9mm thick Door and a 1.2mm thick Frame. This panel is available up to 2000x600mm in a ceiling & wall application.

Fitting

Make sure the structural opening is at least 7mm larger than the panel size, back of frame size. E.G a 600x600mm panel size requires a 607x607mm hole size. Remove the door from the frame and place the frame into the set hole. Fix through the appropriate fixing holes within the frame ensuring the frame is pushed up against the structural opening surround. Check the frame is square by measuring corner to corner. Refit door and lock in place; the door and frame should be flush.

Independent bracing or support may be required to take the weight of the Access Panel.

Apply Intumescent acrylic mastic on both faces of the frame, nominally 5mm wide sealing to the supporting construction.