



LUMIGLAZE

Stylish and contemporary flat glass rooflight

COXDOME LUMIGLAZE

- Ideal for new build and refurbishment projects
- Exceptional noise reduction
- Can be installed onto existing builder's kerbs or preformed upstand
- Uninterrupted glass surface offers pure daylight
- Clear panoramic views internally
- Clean appearance from external roofscape
- Slim aluminium frame profile
- Isolated internally for excellent thermal performance
- Toughened outer glass panel
- Fixing screws concealed with flush cover for invisibility

Product Code	Finished Opening Size (mm)	Overall Glass Size (mm)
CLG6060	600 x 600	750 x 750
CLG6090	600 x 900	750 x 1050
CLG60120	600 x 1200	750 x 1350
CLG7070	700 x 700	850 x 850
CLG8080	800 x 800	950 x 950
CLG9090	900 x 900	1050 x 1050
CLG90120	900 x 1200**	1050 x 1350
CLG100100	1000 x 1000	1150 x 1150
CLG100150	1000 x 1500**	1150 x 1650
CLG100200	1000 x 2000*	1150 x 2150
CLG120120	1200 x 1200**	1350 x 1350
CLG120220	1200 x 2200*	1350 x 2350

*only available as a fixed unit

**These sizes are fitted with two motors in an electric opening dome

Product Specification	
Installation Angle	3-7°
Installation	Screws with cover strip
Frame	Aluminium
Coating	Powder coated aluminium slate grey (RAL 7015)
Drainage	At each corner of the frame
Waterproof welded	At each corner of the frame
Glass Specification	6/12/9.5 6mm clear toughened outer, 12mm argon cavity, 9.5mm clear laminate with Low 'E' as standard, other glazing options available upon request
Insulation (efficiency)	HR++
Insulation (U-value)	1.0 W/M²K°
Insulation (sound)	Approx 35dB
Spacer	Warm edge
LTA/2TA	Approx 69% / 49%
Testing	Fragility, Class B Non Fragile to ACR[M] 001

COXDOME is a UK manufacturer, providing natural daylight and ventilation solutions since 1954



COXDOME part of VELUX Commercial

0121 530 4230
 sales@coxdome.co.uk
 www.coxdome.co.uk