ROSEMARY CLAY CRAFTSMAN

Random textured surfaces, irregular front edge distortion and varying hanging lengths combine to give Rosemary Clay Craftsman the look of traditional handmade clay tiles.



Rosemary Clay Craftsman, Albury, Private House, Cambridge, Cambridgeshire



ROSEMARY CLAY CRAFTSMAN

A unique manufacturing process on a bespoke production line enables tiles to be produced with a heritage look while maintaining all the attributes and strengths of a brand new tile.

TECHNICAL DATA

Size (overall)	265 × 165mm
Minimum Pitch	35°
Maximum Pitch (subject to fixing specification)	90°
Minimum Headlap	Below 90° 65mm / at 90° 35mm
Maximum Headlap	88mm
Minimum Gauge/Batten Spacing	88mm
Maximum Gauge/Batten Spacing	below 90° 100mm / at 90° 115mm
Hanging Length (approx.)	255mm
Cover (all figures are net and do not allow for wastag Linear cover of 1 tile Covering capacity	165mm below 90° 60 tiles/m² / at 90° 52 tiles/m²
Weight per pallet, including pallet (approx.) per 1000	below 90° 78kg/m² / at 90° 68kg/m² 0.95 tonnes 1.30 tonnes
Battens Required (at max.gauge)	below 90° 10.0m/m ²
Batten Size Rafter centres up to 600mm	38 × 25mm
Nail Size for Tiles*	40 x 2.65mm (A/A)
Pallet Quantities Tiles per pallet 720 / Tiles per pack 12 / Packs per pallet 60	
* (A/A) Aluminium Alloy	



KEY ADVANTAGES

- Irregular front edge distortion and varying hanging length
- Replicating look of genuine handmade clay tiles
- Three classic colours

FITTINGS & ACCESSORIES

Ornamental Tile	Club Tiles
Angles	External Angles Internal Angles
Hip	Universal Bonnet Hip Third Round Hip Baby Ridge Dry Hip Rapid Hip
Valley	Valley Tiles 125 GRP Valley Dry Valley
Ridge	Half Round Ridge
Ventilation Systems	RedVent EavesVent RedVent 25 Over-Fascia Vent Rapid Eaves Vent Top Edge Abutment Ventilation DryVent Ridge Continuous Ridge System Uni-Vent Rapid Ridge/Hip RedLine Vent Tile

COLOURS



84 Hawkhurst (Sanded)

(Sanded)

TECHNICAL SOLUTIONS: 03708 702595