DUOPLAIN

DuoPlain combines the classic proportions and good looks of traditional plain tiles with all the time and cost-saving benefits of a modern, large-format, interlocking tile.



DuoPlain, Rustic Black, Private Houses, Lydd, Kent



DUOPLAIN

Engineered for strength, ease of handling and ease of installation, it fulfils the three main demands of a modern roofing tile. Available in seven popular colours.

TECHNICAL DATA

Size (overall)	268 x 330mm
Minimum Pitch (The minimum pitch is based on a maximum rafter length of 10 metres. For rafter lengths greater than this, please contact Technical Solutions on 03708 702595)	
Maximum Pitch (subject to fixing specification)	90°
Minimum Headlap	80mm
Maximum Headlap	95mm
Minimum Gauge/Batten Spacing	173mm
Maximum Gauge/Batten Spacing	188mm
Hanging Length (approx.)	245mm
Cover (all figures are net and do not allow for wastage) Linear cover of 1 tile Covering capacity	300mm 17.7 tiles/m² (at 188mm gauge)
Weight per pallet, including pallet (approx.) per 1000	55kg/m² (at 173mm gauge) 0.91 tonnes 3.10 tonnes
Battens Required (at max. gauge)	5.26m/m ²
Batten Size Rafter centres up to 450mm Rafter centres up to 600mm	38 × 25mm 50 × 25mm
Nail Size for Tiles [*] (Depending on fixing specification)	45 x 3mm (A/A) or 45 x 3.35mm (S/S)
Pallet Quantities Tiles per pallet 28	8 / Tiles per pack 6 / Packs per pallet 48

* (A/A) Aluminium Alloy (S/S) Stainless Steel Ring Shank

COLOURS





KEY ADVANTAGES

- Two 'plain tile' segments give the appearance of a smaller format tile
- Quick and cost-effective to lay
- Seven colour variations to match regional styles and materials

FITTINGS & ACCESSORIES

Ambi-Dry Verge Third Round Hip Baby Ridge Dry Hip Rapid Hip 125 GRP Valley
Baby Ridge Dry Hip Rapid Hip
Úry Hip Rapid Hip
Rapid Hip
125 GRP Valley
Dry Valley
Half Round Ridge
Half Round Monoridge
RedVent EavesVent
RedVent 25 Over-Fascia Vent
Rapid Eaves Vent
Top Edge Abutment Ventilation
DryVent Ridge
DryVent Monoridge
Continuous Ridge System
Uni-Vent Rapid Ridge/Hip