Pasto® sealant

Multi-purpose gun-applied sealant for wet and rough surfaces



*When using on these rough or uneven surfaces, it is recommended that a batten is fixed at the abutment, as shown in diagram 3.

Pasto® is an easy-to-apply sealant, particularly suitable for creating air- and windtight seals between underlays, vapour control layers/air barriers and rough surfaces.

Product features & benefits

- A multi-purpose polyurethane gun-applied sealant
- Highly UV resistant

Area of application

Suitable for:

- Sealing holes in plasterboard ceilings where services pass through vapour control layers/air barriers
- Sealing underlays, vapour control layers/air barriers to rough surfaces eg masonry, abutments and chimneys
- Sealing around nails
- Irregular & rough surfaces
- Timber frame: rough sawn, planed/finished or stained
- Absorbent materials: brick*, sandstone*, concrete* or gypsum fibreboard
- Synthetic materials: paper, fleece or similar, PE*, PP* or hard PVC*
- Other surfaces: metal, glass, PURfoam
- Humidity of 15° or more
- All pitches of roof
- Use both internally & externally

Material

MS polymer

Colour

Grey

Weight (per carton)

6.3kg

Packaging

12 pcs per carton

Product code

KU 0128

Related products

- Any Klober underlay
- Wallint® vapour control layers/air barriers

TECHNICAL DATA

Adhesive	MS Polymer
Solvent	none
Installation temperature	>+5°C/+40°C
Temperature stability	-40°/+80°C
Coverage	310ml tube will cover 10m
UV resistance	Highly resistant
Resistance to ageing	Highly resistant
Shelf life	24 months at 20°C or less

TS-09#16-UK-0114. We assume no liability for typing errors.

Klober Ltd
Unit 6F · East Midlands Distribution Centre · Short Lane · Castle Donington · Derbyshire · DE74 2HA
Tel. +44 (0)1332 813 050 · Fax +44 (0)1332 814 033 · info@klober.co.uk · **www.klober.co.uk**