









# **Description**

A self-adhesive, heat and light reflective tape suitable for use with duct systems on all types of ventilation and air conditioning systems.

#### **Benefits**

- Consistent performance over a wide service temperature range
- · High tack self adhesive bright foil tape
- · High standards of reliability, strength and durability
- · Can be moulded to any profile.

#### Uses

Excellent moisture resistance, suitable for use between foil faced insulation panels in roof and wall applications.

# **Preparation**

Ensure surfaces are sound, clean and dry. Peel required amount of tape off the roll and press firmly in place while unrolling. Tear or cut to length. Do not use on surfaces that bleed oils or plasticisers.

#### Size:

50mm, 75mm and 100mm wide x 45M.

# **Storage Conditions**

12 months in original, unopened packs if stored in dry conditions, out of direct sunlight.

#### **Disposal of Containers**

Do not leave empty packets where waste could be harmful to children, animals or the environment.

#### **Health & Safety**

No major hazard in normal use. Adhesive transfer may cause sensitisation by skin contact, wash skin with soap and water. Keep out of reach of children. Safety data sheet available for professional user on request. It is the users responsibility to determine suitability for use of this product on the right application.

# **Specification Summary**

Foil Thickness	30 microns
Minimum application temperature	0°C
Service range	-15°C to 120°C
Peel Adhesion to Steel	800 N/m

# **Container Sizes**

Code:	BDAT50	BDAT75
Size:	50mm x 45M	75mm x 45M
Barcode:	5060021371553	5060021371638
Code:	BDAT100	
Size:	100mm x 45M	
Barcode:	5060021371645	

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.







Unit G16 River Bank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN. Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310

Email: sales@bond-it.co.uk Website: www.bond-it.co.uk

