

## EUROFAST® H<sub>2</sub>O BARRIER



### QUICK AND EASY A DRY WORKPLACE

Eurofast® H<sub>2</sub>O Barrier water absorption granulate is used to get areas of your gutter or roof covering free of water quickly and easily, in case of maintenance or repair.

By creating a water-tight barrier the water supply is stopped, creating a dry workplace. This makes it possible to work effortlessly.

Within 5 to 10 minutes after the H<sub>2</sub>O Barrier has been scattered around the workplace, a water-tight barrier is created. This barrier is formed by the expansion of the H<sub>2</sub>O Barrier water absorption granulate in the water. The H<sub>2</sub>O Barrier absorbs 200 times its own weight in water.

After use, the water absorption granulate can be easily removed from the surface and disposed into domestic waste. The material of the Eurofast® H<sub>2</sub>O barrier is not harmful to the environment, roof materials or by skin contact.

Packaging	Bucket 1.600 grams incl. Scoop
Absorption capacity	± 400 L of water

#### DIRECTIONS:

1. Scatter a layer twice the height of the standing water around the workplace.
2. If necessary, scatter a thin layer of the water absorption granulate on the workplace.
3. After 5 to 10 min. sweep the thin layer thoroughly towards the barrier, so that the workplace is dry and clean.
4. You can now work.
5. Once finished, dispose of the used granulate in the domestic waste.



SCAN FOR MORE  
INFORMATION