
Manthorpe Building Products

Circular Soffit Ventilator

CODE **G700**







POSITIONING OF G700 FOR 25mm² FREE AIRFLOW

Description:

The G700 Circular Soffit Ventilator is designed to be fitted before or after installation of soffit boards. The airflow passage consists of evenly spaced slots specifically sized to prohibit large insects gaining access but wide enough not to be blocked by debris, paint or water droplets (See BS5250 section 6).

COLOURS	White, Brown, Black, Grey, Golden Oak	
PACKING DETAILS	Packed in 50's in a cardboard box.	
WEIGHT	0.8kg per box	
MATERIAL	Polypropylene	
MANUFACTURING PROCESS	Injection Moulded	
	2150mm² per G700	
FREE AIRFLOW	To achieve 10,000mm ² /M of free airflow the G700 should be fitted at 200mm centres.	
	To achieve 25,000mm ² /M of free airflow the G700 should be fitted at 86mm staggered centres as shown.	





Fitting Instructions:

The G700 Circular Soffit Ventilator (A) should be a "push" fit into a 70mm (2.75") diameter hole drilled into the soffit board as shown.

Use in conjunction with other products from the Manthorpe range to provide a complete roof ventilation system.

Ref	ere	nc	es:
-----	-----	----	-----

BRE: **DIGEST 262/270**

BSI: BS5250

Building Regs F2 DOE: Good Practice Guide NHBC:

NHBC: Standards 7.2

MANTHORPE BUILDING PRODUCTS LTD

MANTHORPE HOUSE **BRITTAIN DRIVE**

CODNOR GATE BUSINESS PARK **RIPLEY**

DERBYSHIRE DE5 3ND

TEL: 01773 303 000

FAX: 01773 303 300

customercare@manthorpebp.co.uk

WEB:

www.manthorpebp.co.uk

DRN M.A Date 20.06.19

The company maintains a policy of continuous development of its product range and reserves the right to amend the specification without notice.

DRG No

Issue

MBP 8006

