



WARNING

Is the correct terminal fitted to your gas flue?

Do not fit

A flue ventilator such as the KYLI2 and KYLI3 which are NOT tested and certified, for use with any live appliance, should only be used on redundant flues.

What should be fitted?

An approved terminal correctly sized for the flue from WT Knowles and Sons.

When should a KNO180 be fitted?

The KNO180 should be used with Gas Fires made to BS 7977 Part 1: 2009 and installed to BS 5871 Part 1: 2005 by a Gas Safe approved installer.

It can also be used for domestic Gas Appliances which have flue outlets up to 125mm diameter.

The KNO180 is one of a range of 14 gas flue terminals available from WT Knowles and Sons which have been tested and certified by Advantica to BS EN 13502:2002

When should a KYK10 be fitted?

The KYK10 is designed to meet all the requirements of BS 5871 Part 3: 2005 Specification for the installation of decorative fuel effect gas appliances and other fuel effect fires and also meets the requirements of The Building Regulations 2010, Approved Document J: Combustion appliances and fuel storage systems.

Suitable for use with flue diameters from 175mm to 225mm.

Technical Information

For any query on the suitability of any WT Knowles and Sons terminal for an intended application please contact the Technical Department on the details below.


Gas can Kill; be Safe not Sorry

Details of all certified and tested gas flue terminals are available on our website

www.wtknowles.co.uk



KYLI2



KNO180



KYK10

