

AEROSANA FLEECE

Fleece for covering cracks or joints



Technical data

Substance	
Material	PET

Attribute	Regulation	Value
Colour		white
Surface weight		63 g/m ²
Thickness		0,7 mm
Tensile strength MD/CD		90 N/5 cm / 145 N/5 cm
Elongation MD/CD		75 % / 90 %
Application temperature		5 °C to 60 °C ; 40 °F to 140 °F

Area of application

AEROSANA FLEECE is a supplementary product for working with spray-on or brush-on seals from the AEROSANA VISCONN family. It can be used to reliably cover cracks or joints that are wider than 3 mm in the case of AEROSANA VISCONN or 20 mm in the case of AEROSANA VISCONN FIBRE.

Forms of delivery

Art. no.	GTIN	Length	Width	Height	Contents	Weight
1AR01715	4026639217158	25 m	150 mm	0	7.5 m ²	0.624 kg

Advantages

- ✓ Reliable airtightness and windtightness: Tested as part of the AEROSANA VISCONN system
- ✓ Easy to work with: Very malleable fleece material
- ✓ Excellent values in the hazardous substance test, has been tested according to the ISO 16000 evaluation scheme

Substrates

AEROSANA FLEECE can be used on subsurfaces that are slightly uneven and/or structured. To achieve airtight and/or windtight installation, it is important that AEROSANA FLEECE is coated with AEROSANA VISCONN or AEROSANA VISCONN FIBRE on both sides in the area where it is in contact with the subsurface.

Recommendations for subsurfaces that AEROSANA VISCONN products can be used on can be found in the relevant application recommendations.



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Ecological Building Systems

For stockist information and full technical support for your project, please contact Ecological Building Systems or visit www.EcologicalBuildingSystems.com



Ireland: 046 9432104 Fax: 046 9432435 UK: 01228 711 511 Fax: 01228 712 280

info@EcologicalBuildingSystems.com