

## Anti-Climb Paint

### PRODUCT DATA

---

#### Description

Anti-climb paint is a thick glutinous coating. In appearance it is similar to smooth gloss paint but when applied remains slippery indefinitely preventing any intruder from gaining a foothold. It is very difficult to remove from hands and clothing. Anti-climb paint continues to work in hot or cold weather conditions adhering to the surfaces to which it is applied.

**Note: As a lawful requirement do not apply under 2m height, users must erect a warning sign after Anti Climb has been applied.**

#### Area of use

Exterior

#### Substrates

Brick, Cement, Wood, Metal, Roof Tiles, Roofing Felt and most Building Materials.

#### Packing

2.5 litres and 5 litres

#### Physical Constants

|                             |                          |
|-----------------------------|--------------------------|
| Colour:                     | Black, Green             |
| Finish:                     | Semi gloss               |
| Volume solids:              | 46%                      |
| Theoretical spreading rate: | 2.5 litres per sq. metre |
| Thickness:                  | 2 – 3 mm                 |
| Flash point:                | 38°C                     |
| Specific gravity:           | 1.10                     |

**\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.**

#### Application Details

|                     |                                                           |
|---------------------|-----------------------------------------------------------|
| Application method: | Stiff Brush, Trowel or by hand wearing protective gloves. |
| Thinner:            | White Spirit                                              |
| Cleaning of tools:  | White Spirit                                              |

|                                 |                                                                                                        |
|---------------------------------|--------------------------------------------------------------------------------------------------------|
| <b><u>Surface condition</u></b> | The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. |
|---------------------------------|--------------------------------------------------------------------------------------------------------|

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

*Please check colour before use. If using multiple cans please check batch numbers are the same.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.