

Bitumen boiler REKORD 19, 29, and 49



- Powerful small bitumen boiler with propane burner

High-performance small bitumen boilers with removable tub. Heating is by means of a windshilded propane vortex beam burner. Construction and fitting comply with the regulations of the German Bau-Berufsgenossenschaft (construction liability insurance).

With the boiler types 19 and 29 the tub can be easily pulled out and used as a bucket. The equipment of the bitumen boiler 49 includes a lockable hinged lid, lackable drain cock, double jacket insulation and, on request, a dial thermometer for temperature control.

Technical data REKORD 19:

Content:	approx. 19 l
Bitumen through-put:	40 l/h
Max. propane consumpt.:	approx. max. 0,6 kg/h
Operating pressure:	1,5 bar
Weight:	approx. 13 kg

Technical data REKORD 29:

Content:	approx. 29 l
Bitumen through-put:	60 l/h
Max. propane consumpt.:	approx. max. 0,8 kg/h
Operating pressure:	1,5 bar
Weight:	approx. 27 kg

Technical data REKORD 49:

Content:	approx. 49 l
Bitumen through-put:	100 l/h
Max. propane consumpt.:	approx. max. 1,4 kg/h
Operating pressure:	1,5 bar
Weight:	approx. 49 kg

Product	Part No.	Figure
---------	----------	--------

Bitumen boiler REKORD 19 l	0201 0000	
----------------------------	-----------	--



Bitumen boiler REKORD 29 l	0202 0000	
----------------------------	-----------	--



Bitumen boiler REKORD 49 l	0203 0000	
----------------------------	-----------	--

