

## HDUTY-P Aluminium Professional Platform Step



[Representative image of product]

### Product Description

Ideal for all professional and commercial use. The TB Davies Professional Platform Step Ladder replaces the classic class 1 step. Our new step ladder complies with current EN131 Professional standards, so you can be assured that you are standing on a top-quality ladder product. The TB Davies Professional Platform Step is a step ladder designed for hard work, day after day. The TB Davies Professional Platform step is manufactured using ribbed aluminium stiles, with a non-slip platform tread, a fitted top tool tray and an integrated hook. The hinges are die-cast and have polyamide/nylon fixings, making the step opening smoother and helping prevent wear and tear. The treads are 85mm deep, offering greater comfort on your feet. The treads are crimped, not riveted, for maximum strength. Our professional steps have one of the broadest size ranges, from 3 to 12 treads. Note, webbing straps fitted on all sizes from 5-treads and above.

### Features

- Aluminium die-cast platform for maximum grip
- Comfortable 85mm welded & crimped treads
- Heavy duty all aluminium construction for longlife
- Fitted with integrated tool tray and hook
- Oversized slip resistant feet provide extra firm footing

### Specifications

- Brand: TB Davies
- Warranty: 5-year
- Max Load: 150kg
- Standard: EN131 PROFESSIONAL
- Material: Aluminium
- Commodity Code: 7616999099
- Country of Origin: IT
- Recommended Usage: Regular

### Common Dimensions

- Tread Depth: 85mm
- Distance Between Treads: 230mm
- Storage Depth: 140mm
- Top Platform Tread (LxW): 330 x 255mm
- Handrail Height: 610mm

### Availability & Delivery

Stock item. Delivery next day.

(See exceptions, if applicable, overleaf)

# HDUTY-P Aluminium Professional Platform Step

## Product Dimensions

SKU	Treads <sup>2</sup>	Approx. Working Height <sup>1</sup> (mm)	Platform Height (mm)	Closed Height (mm)	Width (mm)	Open Depth (mm)	Nett Weight (kg)
1202-023	3	2250	650	1340	440	650	4.5
1202-024	4	2485	885	1565	470	810	5.2
1202-025	5	2720	1120	1810	500	970	6.8
1202-026	6	2955	1355	2055	530	1130	7.5
1202-028	8	3425	1825	2545	590	1480	9.5
1202-030	10	3875	2275	3035	650	1840	12.0
1202-032	12	4360	2760	3525	710	2150	14.2

<sup>1</sup> Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of 75° degrees.

<sup>2</sup> Treads includes top platform step/top cap tool tray tread

## Shipping Dimensions

SKU	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m <sup>3</sup> )	Gross Weight (kg)
1202-023	1380	440	115	0.07	4.50
1202-024	1620	470	115	0.088	5.20
1202-025	1880	500	115	0.108	6.80
1202-026	2120	530	115	0.129	7.50
1202-028	2620	590	115	0.178	9.50
1202-030	3120	650	140	0.284	12.00
1202-032	3620	710	140	0.36	14.20

**Packaging Material** — No Packaging

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.