

DECLARATION OF PERFORMANCE

No. 001001-9050-01

Version : 4

1. Unique identification code of the product-type : **Fibre-cement slates**
(Rivendale, Birkdale, New Stonit, etc.)
2. Type, batch or serial number: **SL 001001**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Roofing - internal wall finishes - external wall and ceiling finishes

4. Name, registered trade name or registered trade mark and contact address of the manufacturer:

Etex Exteriors France
2 rue Charles Edouard Jeanneret
F-78300 Poissy
Manufacturing plants: Saint-Grégoire, 9033

5. Authorised representative: **not applicable**
6. System or systems of assessment and verification of constancy of performance: **System 3**
7. The construction product is covered by a harmonised standard -
CSTB- Notified body N° 0679 performed the fire tests
8. Declared performances:

Essential characteristics	Performance	Harmonised technical specifications
Mechanical resistance (depending on the height h of the slates) h ≤ 350 350 < h ≤ 450 450 < h ≤ 600	Bending Moment (Nm/m) 30 40 45	EN492:2012 + A2:2018
External fire performance	B_{roof}	
Reaction to fire *	A2-s1,d0	
Release of dangerous substances *	-	
Dimensional variations * length width thickness	+/- 3 mm +/- 3 mm +/- 3 mm +25% / -10% of nominal	
Water permeability	no water drops	
Durability against warm water	RL ≥ 0,75	
Durability against soak/dry	RL ≥ 0,75	
Durability against freeze-thaw	RL ≥ 0,75	
Durability against heat-rain	pass	

* Characteristics which apply to fittings. All characteristics apply to slates.

9. The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Date: **05/01/2021**


Jonathan Courcelles
Country manager

CEIDRAL