

**DECLARATION OF PERFORMANCE  
No MFSR/F/2022**

1. Unique identification code of the product-type:  
**Self-adhesive EPDM roof flashing tape Master Flash® Sticky Roll Flat**
2. Intended use/es: **Products exposed to extrinsic factors, glued and mechanically fastened**
3. Manufacturer: **Aztec International S.A., ul. Sowia 13C, 62-080 Tarnowo Podgórne**
4. System/s of AVCP: **System 2+**  
**System 3 (Reaction to fire)**
5. Harmonised standard: **PN-EN 13956:2013-06 Flexible sheets for waterproofing – Plastic and rubber sheets for roof waterproofing – Definitions and characteristics**
6. Notified body: 1434, 1454  
Polskie Centrum Badań i Certyfikacji S.A., Oddział Badań i Certyfikacji w Gdańsku Conducted an inspection of factory and factory production control and inspection surveillance, assessment and evaluation of factory production control system 2 + and issued Certificate of Factory Production Control No 1434-CPR-0252
7. Declared performance/s:


| PARAMETER  | UNIT                       | VALUE                                    | STANDARD   |
|--|----------------------------|--|------------|
| Visible Flaws  | -                          | no                                       | -          |
| Length   | m                          | 5 or 10<br>(0% to +5%)                   | EN 1849-2  |
| Width  | m                          | from 0,15 to 0,60<br>(from -0,5% to +1%) |            |
| Straightness   | mm                         | ≤ 50/10                                  |            |
| Thickness w/o butyl layer  | mm                         | 1,5 (±5%)                                |            |
| Grammage w/o butyl layer   | kg/mm <sup>2</sup>         | 1,690(±5%)                               |            |
| Fire resistance  | class                      | E  | EN 13501   |
| Watertightness   | 10kPa Method B             | Watertight                               | EN 1928    |
| Tensile strength<br>Longitudinal<br>Transverse<br>Elongation<br>Longitudinal<br>Transverse | N/50mm<br>N/50mm<br>%<br>% | ≥200<br>≥350<br>≥50<br>≥29               | EN 12311-2 |
| Static load  | kg                         | ≥20                                      | EN 12730   |
| Impact durability  | mm                         | ≥500                                     | EN 12691   |
| Hail resistance<br>Soft base<br>Hard base  | m/s                        | ≥33<br>≥22                               | EN 13583   |

|  |             |                  |            |
|--|-------------|------------------|------------|
| Tearing resistance<br>Longitudinal<br>Transverse               | N           | ≥80<br>≥140      | EN 12310-2 |
| Peel-off resistance<br>Longitudinal<br>Transverse              | N/50mm      | ≥1,2<br>≥1,1     | EN 12316-2 |
| Shear resistance<br>Longitudinal overlap<br>Transverse overlap | N/50mm      | ≥60<br>≥45       | EN 12317-2 |
| Dimensional stability<br>Longitudinal<br>Transverse            | %           | 0,0<br>0,0       | EN 1107-2  |
| Low temperature<br>bending                                     | °C          | ≥-40             | EN 495-5   |
| UV resistance  | 1000h       | Requirements met | EN 1297    |
| Artificial aging in high<br>temperature                        | 8h<br>100°C | Requirements met |            |

8. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Aztec International S.A.**  
62-080 Tarnowo Podgórne, ul. Sowia 13 C  
tel. 61 867 60 84, fax 61 867 34 44  
NIP 787-19-22-976 REGON 634231705



Adam Gabryś  
Product Engineer  
Tarnowo Podgórne, 21 June 2022.