



Offering a clean, minimalistic finish both inside and out, em.glaze is the elegant go-to solution.

Technical Data

Glazing:

- Double-glazed as standard
- Standard double-glazed glass specification:
 - 6mm Clear toughened outer
 - 16mm Argon filled warm edge spacer silicone bonded
 - 8.8mm laminated inner pane with PVB interlayer (11.5mm on larger units)
- Other glass specifications:
 - Refer to glass specification and performance chart for information relating to other specifications

Frame:

Rooflight frame is manufactured with fully thermally broken design and welded aluminium frame and cill detail. All visible aluminium is polyester powder coated.

Performance – Rooflight:

Refer to glass specification and performance chart and data related to relevant unit size.

Performance – Upstand:


Refer to em.curb data sheet.



Features & Benefits

- Flush glazed glass-to-edge design
- CWCT Class 3 glass tested to BS EN6375-1
- Good thermal and sound insulation properties
- Factory pre-glazed for easy installation
- Ventilation options available
- Compatible with builders and uPVC upstands
- Thermally broken frame
- Aluminium frame powder coated to any RAL colour
- 11 sizes available from stock for delivery within 3-5 working days
- Bespoke units available in 3-5 weeks

Product Diagram



1	Frame	Aluminium
2	Gas	Argon
3	Warm spacer	✓
4	Toughened outer pane	✓
5	Laminated inner pane	✓
6	Thermal break + box section	✓
	Install pitch (upstand)	5–15° recommended
	External frame colour	RAL 7016 anthracite grey or any standard RAL colour
	Ud-value *	1.3
	Airtight BS6375-1:2015 and BS EN 12207	Class 4 300 Pa
	Wind loads BS 6375-1:2015 and BS EN 12210	Class A3

* complete glass unit tested vertically

Testing & Certification

Requirement	Result	Classification
Air Tightness	Class 4 300 Pa	EN12207/ EN1026
Water Tightness	Pass (without penetration of water)	EN 1873
Impact Resistance	CWCT Class 3	-

Guarantee

Whitesales product factories guarantee quality systems implementation process and environmental management systems.

Rooflight Performance

Building Regulations (E&W) Approved Document L compliant design to achieve low U-Values:

- **Ud-Values:** As low as 1.3 W/m²K
- **G-Values:** As low as 0.36
- **Light Transmission:** Up to 80%

Roof Pitch

Recommended to be installed on roof slopes 5-20°.

Options & Accessories

Standard comfort controls:

- For electric opening (see electric opening data sheet)
- Option of retractive switch or comfort kit including a control panel, remote control and rain sensor

Premium comfort controls:

- For electric opening (see electric opening data sheet)
- Wireless controls which include open/close manual switch and internal and external temperature
- Wireless weather station which includes wind and rain sensor
- Option of handheld remote

Product Variations

Ventilation options:

- Available as standard fixed unit
- Electrically opening units operated by slimline chain actuator (see electric opening data sheet)
- Stroke length(mm): 200mm

Cleaning & Maintenance

Any maintenance of rooflights must be carried out strictly in accordance with the relevant 'Health and Safety' regulations.

Glazing: em.glaze rooflights should not be trafficked. Wash and rinse glazing at intervals, to be determined by the owner. Use a solution of 5% mild soap of detergent cleaning solution sprayed on to wash the glazing surface. Follow immediately with clean water and promptly remove excess rinse water with a clean squeegee. DO NOT use abrasive cloth, sponges, cleaner or solvent acid-based solution on the glazing. Should stronger cleaning compounds be needed to remove stubborn stains, consult Whitesales for recommendations.

uPVC Curb: em.curbs are made of shock resistant uPVC which does not need any additional finish. The curbs are equipped with a self-adhesive protection film on the inside, which must be removed at first use. When cleaning the curb, only use non-abrasive and neutral cleaning products, you will keep the smooth inner aspect.

Electric motors: Must be installed by a qualified electrician. Test annually by an Approved Electrical Installations Testing Company. Physically check fixing brackets to ensure fixings are secure.

Note

We reserve the right to make technical changes. For more information on em.glaze and other Whitesales products, visit whitesales.co.uk.

Downloads

For installation instructions, CAD drawings, 3D BIM objects, please visit whitesales.co.uk.

