

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Lead Mate Patination Oil

Revision Date 09.07.2018

Version 3.0

Print Date 09.07.2018



BUILDING TRUST



### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Everbuild Lead Mate Patination Oil

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### 1.3 Details of the supplier of the safety data sheet

Company : Everbuild – A Sika Company  
Site 41  
Knowsthorpe Way  
Cross Green Industrial Estate  
Leeds  
West Yorkshire LS9 0SW  
United Kingdom

Telephone : 0113 240 3456

E-mail address : everbuild.sds@uk.sika.com

#### 1.4 Emergency telephone number

Emergency telephone number : 0044 113 240 3456 (office hours only)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Type of product : Mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3

H226: Flammable liquid and vapour.

Specific target organ toxicity - repeated exposure, Category 1, Central nervous system

H372: Causes damage to organs through prolonged or repeated exposure if inhaled.

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Lead Mate Patination Oil

Revision Date 09.07.2018

Version 3.0

Print Date 09.07.2018



BUILDING TRUST



Hazard statements	: H226 H372  H304	Flammable liquid and vapour. Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled. May be fatal if swallowed and enters airways.
Supplemental Hazard Statements	: EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary statements	: P101  P102 <b>Prevention:</b> P210  P260  <b>Response:</b> P370 + P378  <b>Disposal:</b> P501	If medical advice is needed, have product container or label at hand. Keep out of reach of children.  Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.  Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

- 919-164-8 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

### Additional Labelling:

EUH208 Contains 2-butanone oxime. May produce an allergic reaction.

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical name CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)  919-164-8 265-185-4 01-2119473977-17-XXXX [corresponding group CAS	STOT RE1; H372 Asp. Tox.1; H304	>=80

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Lead Mate Patination Oil

Revision Date 09.07.2018

Version 3.0

Print Date 09.07.2018



BUILDING TRUST



64742-82-1]		
2-butanone oxime 96-29-7 202-496-6 01-2119539477-28-XXXX	Carc.2; H351 Acute Tox.4; H312 Eye Dam.1; H318 Skin Sens.1; H317	< 1

For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Erythema  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : No known significant effects or hazards.
- Causes damage to organs through prolonged or repeated exposure if inhaled.  
Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Lead Mate Patination Oil

Revision Date 09.07.2018

Version 3.0

Print Date 09.07.2018



BUILDING TRUST



Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO<sub>2</sub>), Dry chemical

Unsuitable extinguishing media : Water

### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drink-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Lead Mate Patination Oil

Revision Date 09.07.2018

Version 3.0

Print Date 09.07.2018



BUILDING TRUST



ing should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Store in accordance with local regulations.

Other data : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (0,4 mm),  
Contaminated gloves should be removed.  
Suitable for permanent exposure:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Lead Mate Patination Oil

Revision Date 09.07.2018

Version 3.0



BUILDING TRUST



Print Date 09.07.2018

Viton gloves (0.4 mm),  
breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : No special measures required.

### Environmental exposure controls

General advice : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : liquid  
Colour : yellow  
Odour : characteristic  
Odour Threshold : No data available  
Flash point : ca. 38 °C  
Autoignition temperature : No data available  
Decomposition temperature : No data available  
Lower explosion limit (Vol-%) : 0,6 %(V)  
Upper explosion limit (Vol-%) : 6,5 %(V)  
Flammability : No data available  
Explosive properties : No data available  
Oxidizing properties : No data available  
pH : No data available  
Melting point/range / Freezing point : No data available  
Boiling point/boiling range : 152 °C  
Vapour pressure : 3,9997 hPa

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Lead Mate Patination Oil

Revision Date 09.07.2018

Version 3.0

Print Date 09.07.2018



BUILDING TRUST



Density	:	ca.0,882 g/cm3 at 20 °C
Water solubility	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	< 20,5 mm2/s at 40 °C
Relative vapour density	:	No data available
Evaporation rate	:	No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

#### Components:

**2-butanone oxime:**

Country GB 100000009104

7 / 12

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Lead Mate Patination Oil

Revision Date 09.07.2018

Version 3.0

Print Date 09.07.2018



BUILDING TRUST



Acute oral toxicity : LD50 Oral (Rat): 3.680 mg/kg

### Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

### Serious eye damage/eye irritation

Not classified based on available information.

### Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

Not classified based on available information.

### STOT - repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

### Aspiration toxicity

Not classified based on available information.

## SECTION 12: Ecological information

### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Lead Mate Patination Oil

Revision Date 09.07.2018

Version 3.0

Print Date 09.07.2018



BUILDING TRUST



### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

## SECTION 14: Transport information

### ADR

14.1 UN number : 1993  
14.2 UN proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(naphtha (petroleum))  
14.3 Transport hazard class(es) : 3  
14.4 Packing group : III  
Classification Code : F1  
Labels : 3  
Tunnel restriction code : (D/E)  
14.5 Environmental hazards : no

### IATA

14.1 UN number : 1993  
14.2 UN proper shipping name : Flammable liquid, n.o.s.  
(naphtha (petroleum))  
14.3 Transport hazard class(es) : 3  
14.4 Packing group : III  
Labels : 3

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Lead Mate Patination Oil

Revision Date 09.07.2018

Version 3.0

Print Date 09.07.2018



BUILDING TRUST



**14.5 Environmental hazards** : no

### IMDG

**14.1 UN number** : 1993

**14.2 UN proper shipping name** : FLAMMABLE LIQUID, N.O.S.  
(naphtha (petroleum))

**14.3 Class** : 3

**14.4 Packing group** : III

Labels : 3

EmS Number 1 : F-E

EmS Number 2 : S-E

**14.5 Marine pollutant** : no

### 14.6 Special precautions for user

No data available

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Prohibition/Restriction

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed  
(=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
(3)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

REACH Information: All substances contained in our Products are  
- registered by our upstream suppliers, and/or  
- registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.



P5c

FLAMMABLE LIQUIDS

Quantity 1  
5.000 t

Quantity 2  
50.000 t

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Lead Mate Patination Oil

Revision Date 09.07.2018

Version 3.0

Print Date 09.07.2018



BUILDING TRUST



VOC-CH (VOCV)	: 99,01 %
VOC-EU (solvent)	: 99,01 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations  
Health and Safety at Work Act 1974 & Subsidiary Regulations  
Control of Substances Hazardous to Health Regulations (COSHH)  
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

### Full text of H-Statements

H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure if inhaled.
H412	Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	Acute toxicity
Aquatic Chronic	Long-term (chronic) aquatic hazard
Asp. Tox.	Aspiration hazard
Carc.	Carcinogenicity
Eye Dam.	Serious eye damage
Skin Sens.	Skin sensitisation
STOT RE	Specific target organ toxicity - repeated exposure
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	Chemical Abstracts Service
DNEL	Derived no-effect level
EC50	Half maximal effective concentration
GHS	Globally Harmonized System
IATA	International Air Transport Association
IMDG	International Maritime Code for Dangerous Goods
LD50	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	International Convention for the Prevention of Pollution from Ships,

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Lead Mate Patination Oil

Revision Date 09.07.2018

Version 3.0

Print Date 09.07.2018



BUILDING TRUST



OEL	1973 as modified by the Protocol of 1978
PBT	Occupational Exposure Limit
PNEC	Persistent, bioaccumulative and toxic
REACH	Predicted no effect concentration
	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	Substances of Very High Concern
vPvB	Very persistent and very bioaccumulative

### Classification of the mixture:

Flam. Liq. 3	H226
STOT RE 1	H372
Aquatic Chronic 3	H412

### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !