





Leafguards for use with rainwater outlets

### Application

• For use with FarBo<sup>®</sup> rainwater outlets, to prevent the blocking of the outlet by debris

### **Key Features**

- Many types available to suit most applications
- Durable and hard wearing



03 ROOF DRAINAGE SYSTEMS Leafguards

### **Universal leafguard**

Code	To suit pipe size (mm)	Guard size (mm)	For use with	
FO-UG-210	50-160	210 x 210	FloDrain (with exception of FO-FLO-40	
FO-UG-325	160-250	325 x 325	DuoDrain	

Stainless steel universal guard is solid and effective and securely clamps to the inside of the outlet stem. It is also tamper proof, as it can only be removed with the correct tool

PAULON AND AND AND AND AND AND AND AND AND AN	
Universal leafguard	

### **CasCade leafguard**

Code	To suit pipe size (mm)	Guard size (mm)	For use with
FO-CASCADE	50-160	260 x 260	FloDrain (with exception of FO-FLO-40) DuoDrain

The FarBo CasCade is a new, high performance leaf guard, manufactured from 304 grade stainless steel. Designed for use with standard size FarBo roof outlets, the new design dramatically increases the flow rate by over 50% compared to standard leaf guards. The leaf guard is also tamper resistant, as it can only be removed from the outlet by using a spanner.

and the second sec
CasCade leafguard

### Monsoon leafguard

Code	To suit pipe size (mm)	Guard size (mm)	For use with		
FO-MONSOON	50-160	245 x 245	FloDrain (with exception of FO-FLO-40) DuoDrain		
New development designed to maximise flow rates through standard size drainage systems. Tamper proof, as it					

New development designed to maximise flow rates through standard size drainage systems. Tamper proof, as it can only be removed with the correct tool.



Click leafguard					
Code	To suit pipe size (mm)	Guard size (mm)	For use with		
FO-CLICK	70-180	205	FloDrain sizes FO-FLO-70 through to FO-FLO-160 DuoDrain		
Provides solution for	Provides solution for applications where maintenance is required on a regular basis. Simple ratchet system allows				

Provides solution for applications where maintenance is required on a regular basis. Simple ratchet system allows quick and tool free removal of guard.





Number 10905 ISO 9001: 2008 ISO 14001: 2004 BS OHSAS 18001: 2007

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218. The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY

© Fixfast July 2017. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.

Cylindrical leafguard					
Code	To suit pipe size (mm)	Guard size (mm)	Guard height (from deck level - mm)	For use with	
FO-CG-50	50	50			
FO-CG-62	62	62			
FO-CG-70	70	70			
FO-CG-75	75	75	105		
FO-CG-80	80	80		FloDrain	
FO-CG-95	95	95		DuoDrain	
FO-CG-110	110	110			
FO-CG-125	125	125			
FO-CG-145	145	145			
FO-CG-160	160	160			



Stainless steel cylindrical leafguard ideal for use in restricted areas and for ballasted roofs. Ten standard sizes are available, please specify when ordering.

### **Balconv** leafquard

Code	To suit pipe size (mm)	Guard size (mm)	For use with			
FO-BG	50-110	135 x 135	For all drains within the sizes below: 50-110			
Very low profile, making it suitable for balconies and other areas which are exposed to light foot traffic						



### Wire ball leafguard

Code	To suit pipe size (mm)	Guard size (mm)	For use with
FO-WB	50-110	132 x 132	For all drains within the sizes below:
FO-LWB	110-160	185 x 185	50-160

Plastic coated wire ball leafguard is effective and economical. Prevents small debris from entering the roof outlets.





Number 10905 ISO 9001: 2008 ISO 14001: 2004 BS OHSAS 18001: 2007

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218. The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY

© Fixfast July 2017. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



### ParaDrain leafquard

Code	To suit pipe size (mm)	Guard size (mm)	For use with		
FO-PG-225	50-110	225 x 100 x 140	All ParaDrain sizes		
FO-PG-325	110-160	325 x 100 x 140	All Parabrail Sizes		
Stainless steel parapet leafguard prevents blocking of outlet by debris					



Para Click leatguard					
Code	To suit pipe size (mm)	Guard size (mm)	For use with		
FO-PG-CLICK	50-110	230 x 100 x 225	All ParaDrain sizes		

Provides solution for applications where maintenance is required on a regular basis. Simple ratchet system allows quick and tool free removal of guard.





Ballast leafguard					
Code	To suit pipe size (mm)	Guard size (mm)	Guard height (from deck level - mm)	For use with	
FO-BSG-62	62	62			
FO-BSG-70	70	70		FloDrain	
FO-BSG-75	75	75			
FO-BSG-80	80	80	260	DuoDrain	
FO-BSG-95	95	95			
FO-BSG-110	110	110			
			0		

Stainless steel cylindrical leafguard ideal for use on ballasted roofs. Six standard sizes are available, please specify when ordering.





ISO 9001: 2008

ISO 14001: 2004 BS OHSAS 18001: 2007

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218. The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY

© Fixfast July 2017. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.