

# FLEXPOL GREY

**ROOF  
FLEX**<sup>®</sup>

**USE  
WHEN DAMP  
OR DRY**

- Fibre reinforced emergency roof repair compound
- Instant waterproofing
- Single coat application - brush applied

Roof Flex Flexpol is a solvent based acrylic coating, incorporating synthetic fibres, and is designed specifically for the long term maintenance of domestic and industrial roofs. The product provides a tough yet flexible seamless coating with excellent crack bridging properties.

Ensure that all surfaces are clean, dry and free from oil, grease dirt and organic growth. All traces of organic growth should be removed using a stiff bristle brush or low pressure water jet. The surface should then be treated with a proprietary fungicidal wash. Any metal surfaces showing advanced signs of corrosion should be treated with a rust inhibitor such as red oxide. Any remedial work to the substrate should be completed prior to the application of surface coatings. Flexpol is not for use on polycarbonate roofs.

Porous surfaces should be treated with a coating of Bitumen Primer and allowed to dry thoroughly.

Roof Flex Flexpol is applied to the prepared substrate by brush at the recommended rate of 1-2kg/m<sup>2</sup>, ensuring an even coverage free from pinholes. The product will fill and bridge cracks up to 10 mm wide, but where wider cracks are present these should be covered with a suitable flexible scrim bedded into the coating. On damp substrates Roof Flex Flexpol should first be worked into the surface with a brush to disperse excess moisture and ensure a good bond. Immediately afterwards, further product is then brushed onto the surface. After use clean all equipment immediately with White Spirit.

Care should be taken to avoid contact with skin and eyes. Ensure adequate ventilation and do not smoke when using the product. Store in a cool, dry place away from sources of ignition or naked flames. Shelf life is a minimum of 12 months in unopened, sealed containers. DISPOSAL: Do not empty into drains. Remove excess product from tools before cleaning. Some local authorities have special facilities for the disposal of waste liquids.

## WARNING

Flammable liquid and vapour.  
May cause harm to breast-fed children.  
Toxic to aquatic life with long lasting effects.  
Repeated exposure may cause skin dryness or cracking  
Keep out of reach of children.  
Take precautionary measures against static discharge.  
Wash skin thoroughly after handling.  
Wear protective gloves/protective clothing/eye protection/ face protection.  
IF ON SKIN (or hair): Remove immediately all contaminated clothing.  
Rinse skin with water/shower.  
IF exposed or concerned: Get medical advice/attention.  
In case of fire: Use water spray, water mist, powder, foam, carbon dioxide for extinction.  
Do not empty into drains. Avoid release to the environment.

For further information refer to **Safety Data Sheet** at [www.roof-flex.co.uk](http://www.roof-flex.co.uk).



**FLEXPOL • UN 1263 • VOC (Cat.2(i)): 500g/l(2010) • VOCs (g/L): 459**

**5 kg**

Radmat Building Products Ltd, Holland House, Valley Way, Rockingham Road, Market Harborough, Leicestershire, LE16 7PS. Tel: 01858 412109