



+44 (0)1327 701910 | sales@hambleside-danelaw.co.uk | www.hambleside-danelaw.co.uk

3-IN-1 EAVES VENTILATION PACK

15 YEAR GUARANTEE

The pack ensures that all required elements of an eaves to eaves ventilation system are provided.

FEATURES AND BENEFITS

- When fitted to roofs of all pitches the system will provide continuous opening equivalent of 10,000mm²
- Meets Building Regulation requirements
- For roof pitches above 15°

PACK CODE AND SIZE

HD 3000VP - 6 metres

PACK COMPONENTS



Over Fascia Vent* Code: HD 12000M Provides a through flow of ventilating air equivalent to an opening of 10,000mm² per metre. 6 x 1m lengths



Universal Roll Panel Vent* Code: HD 5000 The roll is suitable for use on all roof pitches and meets requirements for either 10,000mm² or 25,000mm² equivalent opening per metre. Due to its design it may be fitted to all rafter centres. 1 x 6m roll

Roofing Underlay Support Tray*

Provides full support and eaves

protection for roofing underlay

at eaves level and combines to provide drip into the guttering.

The design allows it to clip

together for universal rafter

spacing. 10 x 600mm lengths

Code: HD 3000



*Products also available separately

INSTALLATION

The over fascia ventilator (HD 12000M) is fixed in position on top of the fascia board through the reinforced nail guides. The roll panel (HD 5000) is fitted in accordance with the area of contact be made by the insulation quilt to the underside of the underlay. It is tack nailed or stapled to the rafters at the appropriate height.

The underlay support eaves tray (HD 3000) is placed on top of the over fascia ventilator and secured in place by nailing through the guide holes in the over fascia ventilator.

ALTERNATIVE PACK

Code: HD 3025VP

This pack will provide continuous opening equivalent of 10,000mm² or 25,000mm² per metre. This pack is fitted in the same manner but contains the HD 12000U ventilator instead of the HD 12000M.



Universal Over Fascia Vent* Code: HD 12000U 10,000mm² continuous opening per metre for roof pitches above 15 and 25,000mm² for pitches below 15°, for warm roof applications and where ventilating above a breathable underlay. 6 x 1m lengths

RELATED PRODUCTS



CON6+ Universal Ridge and Hip System Includes a ventilated membrane with broad corrugated adhesive strips, patented gaskets, stainless steel straps and fixing screws, code: HD CON6



Tile and Slate Ventilators

Wide range of flush fitted ventilators for tiles and slates, available in up to five different colours. Also available are a selection of hooded slate ventilators.



Tile & Slate Breathable Roofing Underlays Available in four weights and widths of 1.0m or 1.5m, two with optional integral lap tapes, codes: HD DLR120, DLR120TT, DLR135, DLR150, DLR150TT and DLR180

