



CONTI-SOAKERS

30 YEAR GUARANTEE

The continuous GRP soakers provide a quick and efficient method of forming a secret gutter or weatherproof solution at the tile or slate roof side abutment junction.



FEATURES AND BENEFITS

- Quick and simple to install
- Thermally stable
- UV and acid rain resistant
- Lead alternative
- Reduced theft risk
- Creates no harmful run off into water courses
- Mortar bonding strip for tile roof application
- Dry fix products eliminate the mortar installation and maintenance issues

APPLICATION

The range of GRP Conti-Soakers for tile and slate roofs are available in lipped and unlipped options. The lipped version is fixed directly into the wall, alternatively the unlipped version can be installed with a stepped or GRP cover flashing.

The Conti-Soaker for Scottish slate roofs is supplied unlipped and installed in the same way.

MATERIAL AND COLOUR


GRP and Anthracite

CERTIFICATION


BBA Certificate 87/1915




PRODUCT, CODE AND DIMENSIONS




For tile roofs, code: HD CST-L
Dimensions: H150 x W170 x L3000mm



For tile roofs, code: HD CST
Dimensions: H140 x W170 x L3000mm



For slate roofs, code: HD CSS-L
Dimensions: H150 x W170 x L3000mm



For slate roofs, code: HD CSS
Dimensions: H140 x W170 x L3000mm



For Scottish slate roofs, code: HD SCSS
Dimensions: H200 x W160 x L3000mm

♻️ Contains recycled glass

RELATED PRODUCTS

