

Heavy Duty Elastomeric Floor Coating

PRODUCT DATA

Description:

Formulated with thermo-acrylic and polyurethane resins for long-term durability in high traffic areas. Flexible to accommodate surface movement and resist cracking. Reinforced with Dolomite stone for a fine-textured, anti-slip* finish. Suitable for car parks, walkways, industrial floors, driveways, balconies, and other heavily used concrete surfaces.

***Important Note: This product has anti-slip properties and therefore provides slip resistance, however, it is not possible to guarantee a totally non-slip surface.**

Sealing / Priming

It is only necessary to seal a porous substrate such as new or bare concrete. A sealer coat is achieved by adding 10% HD Thinner to the paint. Please note new concrete floors can only be painted after 6-8 weeks.

Area of use:

Internal and External

Substrates:

Concrete, Stone, Tarmac & Asphalt (if suitably aged), Ferrous Metals, Wood

Packing:

2.5 Litres, 5 Litres & 20 Litres

Physical Constants:

Colour:	Red, Grey, Mid Grey, Green, Blue, Black and Safety Yellow
Finish:	Satin
Volume solids:	55%
Theoretical spreading rate:	10 - 12 sq.metres per litre
Flash point:	42°C
Specific gravity:	1.22
Dry to touch:	2 Hours
Over-coating time:	24 Hours

****The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.***

Application Details:

Application method:	Brush or Roller
Thinner:	HD Thinners
Cleaning of tools:	HD Thinners

Surface Condition:

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

For additional guidance (eg. power-floated floors, existing coatings, possible existing contamination etc.) please contact your local Technical Sales Representative. Please check colour before use. If using multiple cans please check batch numbers are the same.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.