



Res-Lead Master Flash®

“Protective Coated Safe Lead”

Two Compounds / 4 Sizes.

Advanced Ozone Resistance tested to...		EPDM 70 hour @ 500 pphm	HIGH TEMP RED SILICONE 70 hour @ 500 pphm
High Temperature Resistance Tested to	Intermittent	+135°C (+275°F)	+260°C (+500°F)
	Continuous	+100°C (+212°F)	+225°C (+437°F)
Low Temperature Resistance tested to...		- 55°C (-67°F)	- 74°C (-101°F)
Compression Set Maximum...		25%	50%

*Complete specification data and testing methods are available upon request.

A “C20” ASTM

additional requirement was added to assure conformance to the most stringent ozone/weathering specifications available. This addition allows the rubber a 20 year life.

Weather Protection


Made of EPDM or High Temp Red Silicone,

These flashings are compounded specifically for maximum resistance to weathering due too zone and ultraviolet light.




Clay Tiles

**20
YEAR
WARRANTY**




Mini Res-Lead Flashing Details

A-Top Opening	Closed
B-Pull to suit pipe size	1/4"-3" (6-76mm)
C-Base	16"x19-1/4" (410x490mm)




#1 Res-Lead Flashing Details

A-Top Opening	2-1/2" (63mm)
B-Pull to suit pipe size	3"-8" (76-203mm)
C-Base	20"x24" (508x609mm)



#2 Res-Lead Flashing Details

A-Top Opening	5-5/8" (142mm)
B-Pull to suit pipe size	8"-11" (203-279mm)
C-Base	26"x30" (660x762mm)



#3 Res-Lead Flashing Details

A-Top Opening	8-3/4" (222mm)
B-Pull to suit pipe size	11"-18" (279-457mm)
C-Base	35"x 35" (889x889mm)



This product can expose you to certain chemicals, which are known to the State of California to cause cancer or birth defects to other reproductive harm. For more information go to: www.P65Warnings.ca.gov