CE



Declaration of Performance

Kingspan Kooltherm® K107 Pitched Roof Board

1000.CPR.2013.K107.006

Unique identification code of the product-type: Intended use/es: Manufacturer: System/s of AVCP: Harmonised technical specification Notified body/ies: Kingspan Kooltherm[®] K107 Pitched Roof Board Thermal insulation for buildings Kingspan Insulation Ltd, Herefordshire HR6 9LA, UK System 4 (Reaction to fire), System 3 (Other Properties) BS-EN 13166:2012+A2:2016 KIWA:1640, FIW:0751

| Essential characteristics | | Performance |
|--|---|--|
| Thermal resistance | Thermal resistance R _D ((m².K)/W) | $\begin{array}{ccccc} d_N & 25mm & 1.30 \\ d_N & 30mm & 1.55 \\ d_N & 40mm & 2.10 \\ d_N & 50mm & 2.60 \\ d_N & 60mm & 3.15 \\ d_N & 70mm & 3.65 \\ d_N & 70mm & 3.65 \\ d_N & 75mm & 3.90 \\ d_N & 80mm & 4.20 \\ d_N & 90mm & 4.70 \\ d_N & 100mm & 5.25 \\ d_N & 100mm & 5.25 \\ d_N & 110mm & 5.75 \\ d_N & 120mm & 6.30 \\ d_N & 130mm & 6.80 \\ d_N & 140mm & 7.35 \\ d_N & 150mm & 7.85 \\ \end{array}$ |
| | Thermal conductivity λ_D (W/(m.K)) | λ _D 0.019 |
| | Thickness tolerance | Т1 |
| Reaction to fire | Reaction to fire | F |
| Durability of reaction to fire against heat, weathering, ageing / degradation | Durability Characteristics | NPD |
| Durability of thermal resistance against heat, weathering, ageing/ degradation | Durability Characteristics | NPD |
| | Dimensional stability under specified temperature and humidity condition | DS(70,90) |
| | | DS(-20,-) |
| | Determination of the aged values of thermal resistance and thermal conductivity | R_D and λ_D |



Declaration of Performance

| Compressive strength | Compressive stress or compressive strength | CS(Y)100 | |
|--|--|----------|--|
| Tensile / Flexural strength | Tensile strength perpendicular to faces | NPD | |
| Durability of compressive strength against ageing / degradation | Compressive creep | NPD | |
| Water permeability | Short term water absorption | NPD | |
| | Long term water absorption | NPD | |
| | Closed cell content | CV | |
| Water vapour permeability | Water vapour transmission | NPD | |
| | Closed cell content | NPD | |
| Release of dangerous substances to the indoor environment | Release of dangerous substances | NPD | |
| Continuous Glowing Combustion | Glowing combustion | NPD | |
| NPD: No Performance Determined | | | |

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Aisen Key

Aiveen Kearney Managing Director Pembridge, England, UK Date signed: 08/08/2022 Version Number: 006

KI\GB\CPRDoP\K107\006\Aug22a