



Declaration of Performance

Kooltherm® K15

1002.CPR.2013.K15.009

Unique identification code of the product-type: Kooltherm® K15

Intended use/es:

Thermal insulation for buildings

Manufacturer: Kingspan Insulation Ltd, Bree Industrial Estate, Castleblayney,

Co Monaghan, Ireland A75 X966

System/s of AVCP: System 1 (Reaction to Fire), System 3 for all other characteristics

Designated technical specification: EN 13166:2012+A2:2016

Notified body(ies) : KIWA BDA (NB 1640), Efectis (NB 1812)

| Essential characteristics | | Performance | |
|--|--|---|--|
| Thermal resistance | Thermal resistance R _D ((m².K)/W) | d _N 25mm 1.10 d _N 30mm 1.35 d _N 40mm 1.80 d _N 50mm 2.35 d _N 60mm 2.85 d _N 70mm 3.30 d _N 80mm 3.80 d _N 90mm 4.25 d _N 110mm 5.20 d _N 120mm 5.70 d _N 130mm 6.15 d _N 140mm 6.65 d _N 150mm 7.10 | |
| | Thermal conductivity λ _D (W/(m.K)) | d _N 25-44mm 0.022 d _N 45-150mm 0.021 | |
| | Thickness tolerance | Т1 | |
| Reaction to fire | Reaction to fire | C-s2,d0 | |
| Durability of reaction to fire against heat, weathering, ageing / degradation | Durability Characteristics | NPD | |
| Durability of thermal resistance against heat, weathering, ageing/ degradation | Durability Characteristics | NPD | |
| | Dimensional stability under specified temperature and humidity condition | DS(70,90) | |
| | | DS(-20,-) | |
| | Thermal conductivity λ _D (W/(m.K)) | d _N 25-44mm 0.022 d _N 45-150mm 0.021 | |





Declaration of Performance

| | Determination of the aged values of thermal resistance and thermal conductivity | RD and λD | |
|---|---|-----------|--|
| Compressive strength | Compressive stress or compressive strength | CS(Y)100 | |
| Tensile / Flexural strength | Tensile strength perpendicular to faces | NPD | |
| Durability of compressive strength against ageing / degradation | Compressive creep | NPD | |
| Water permeability | Short term water absorption | NPD | |
| | Long term water absorption | NPD | |
| | Closed cell content | CV | |
| Water vapour permeability | Water vapour transmission | NPD | |
| | Closed cell content | NPD | |
| Continuous Glowing Combustion | Glowing Combustion | NPD | |
| Release of dangerous substances to the indoor environment | Release of dangerous substances | NPD | |
| NPD: No Performance Determined | | | |

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Aiveen Kearney

Managing Director, Ireland Date signed: 5th December 2022 Issue Number: 009

KI\IE\DoP\CPR\K15\009\Dec22a