Introducing the cutting-edge One2Clean treatment plant range



Setting the standard

ADVANCED TECHNOLOGY

The go to treatment plant for Nutrient Neutrality. Unrivalled effluent quality. Treatment levels -BOD – 7mg/l Suspended Solids – 14mg/l Ammonia – 0.5mg/l Phosphate – 1.6mg/l Nitrate – 7.9mg/l

PRODUCT QUALITY

German engineering.



SUSTAINABILITY

Low power consumption - Daily energy usage of your One2clean treatment plant – from 0.59kWh.

Quiet operation – High quality diaphragm compressors.

CUSTOMER SERVICE

Lifetime support – Customer support on your project from start to finish. **GRAFter network** – Graf accredited service provider network for all your service and maintenance needs.



Graf UK will arrange FREE commissioning of your system by a Graf accredited service provider who will register your system to activate your warranty. For more information go to https://bit.ly/GRAFFreeCommission or scan the QR code



GRAF





For general enquiries go to https://bit.ly/grafuksts or scan the QR code

The one2clean system

The only wastewater underground tank of it's kind!







3. Clear water extraction without delay. The treated clear water is extracted from the system

and the cleaning process can begin once more.





one2clean only needs 3 steps to produce clear water

The wastewater treatment is carried out in one chamber in just one tank. This eliminates unnecessary pumping processes and sludge return.

One-tank system

2. Settling phase

Aeration is interrupted by the control unit, the activated sludge sinks to the bottom. A clear water zone develops in the upper part of the container.

1. Wastewater treatment

The wastewater arrives

directly in the biological

zone without the need

for pumping processes.

Aeration of the entire

immediate wastewater activation. The micro-

biological cleaning process

organisms begin the

container leads to

one2clean is odourless

The entire volume of wastewater is immediately activated with oxygen using the unique one2clean technology. The final process of the one2clean produces an odourless, clear treated water for extraction to soakaway or waterway.

Incredibly low volume of sewage sludge

- Aeration of the entire wastewater tank
- Immediate wastewater activation
- Minimisation of the sludge
- Less sludge removal
- Cost savings

Conventional wastewater treatment systems

one**2clean**





Minimum maintenance costs

- Simple construction
- High-quality components
- As much technology as necessary, as little technology as possible.
- Integrated sampling point

Minimum power consumption

- one2clean has only one pumping process, reducing energy consumption and running costs
- Economical motor valve
- Energy-optimised membrane compressor

one2clean already meets the needs of tomorrow

one2clean achieves sustainable discharge values with an efficiency factor of up to 99%! This offers high investment security – even if legal requirements become stricter.

Inhabitants [max.]	Standard control system	Advanced control system	Max. daily flow [l/d]	Max. organic load [kg BOD5/d]	Total volume [l]	Length [mm]	Width [mm]	Height [mm]	Weight [kg]	Product code
5	1	1	750	0.3	3,750	2280	1755	1880	150	G50000
7	1	1	1,050	0.42	4,800	2280	1985	2110	185	G50002
9	✓	1	1,350	0.54	6,500	2390	2190	2390	220	G50004
12	1	1	1,800	0.72	8,500	3500	2040	2515	380	G50200
15	1	1	2,250	0.9	10,000	3520	2240	2575	455	G50204
24	×	1	3,600	1.44	16,000	4590	2500	3160	890	106261
32	×	1	4,800	1.92	22,000	6230	2500	3160	1085	106262
45	×	1	6,750	2.70	32,000	8440	2500	3160	1430	106264
50	×	1	7,500	3.00	38,000	9925	2500	3160	1630	106265
60	×	1	9,000	3.60	44,000	11440	2500	3160	1840	106064
70	×	1	10,500	4.20	48,000	12140	2500	3160	1970	106359

Two-tank system

Inhabitants [max.]	Standard control system	Advanced control system	Max. daily flow [l/d]	Max. organic load [kg BOD5/d]	Total volume [l]	Length [mm]	Width [mm]	Height [mm]	Weight [kg]	Product code
10	1	1	1,500	0.6	7,500	5160	1755	1880	300	G50006
14	1	1	2,100	0.84	9,600	5160	1985	2110	370	G50008
18	1	1	2,700	1.08	13,000	5380	2190	2390	440	G50010

Advanced control system incorporates an advanced Control M controller with plug and play options.