



Pedrina Prime



For those seeking a subtly greyer aesthetic, Pedrina offers an ideal solution. Its rich blue-grey undertones, combined with a pronounced, textured surface, ensure a consistently striking and refined roof finish.



Product information



Product profile

Pedrina Prime slate displays a distinctive blue-grey shade with a bold, naturally textured surface, closely resembling the look of slate from the Ffestiniog Welsh quarry.

Quarried in Spain's Orense region—well known for its production of high-quality roofing slate—Pedrina Prime is hand-crafted to ensure lasting strength and refined finish. It complies with BS EN 12326 standards, achieving premium classifications of "W1-T1-S1".*

* Test results are available on request

Guarantee

Each slate is supported by a 75-year guarantee, reflecting its proven quality and long-term performance.**

** Guarantees to be requested within 6 months of the date of completion of the roof.

Minimum headlap for fixing slates with nails or hooks according to BS 5534: 2014+A2:2018 Code of Practice for Slating and Tiling
Moderate exposure (< 56.5 l/m² per spell)*

Size (mm)	Rafter pitch								
	20°	22.5°	25°	27.5°	30°	35°	40°	45°	80°
500 x 250	–	–	120	100	80	70	60	55	50

Severe exposure (≥ 56.5 l/m² per spell)*

Size (mm)	Rafter pitch								
	20°	22.5°	25°	27.5°	30°	35°	40°	45°	80°
500 x 250	–	–	–	130	100	90	80	70	65

Size and weight

Size (mm)	Thickness (mm)	Weight per 1000 (kg)
500 x 250	5 - 6	2100

The information, both technical and otherwise contained within this guide, is intended to provide illustrations on some of the ways in which SSQ products may be used and should be read in conjunction with all relevant British Standards, Codes of Practice and Health and Safety Legislation. Nothing contained in this brochure nor any advice or recommendation given by or on behalf of SSQ is intended to be relied upon in substitution for an appropriate technical and design appraisal of the specific use to which SSQ products will be put. SSQ will accept no responsibility for any loss or damage howsoever caused that may arise through the reliance being placed on the content of the brochure.

SSQ reserve the right to change designs and specifications without prior notice. All products are subject to our Terms of Business, available on request.
The information and illustrations in this publication were correct at the time of publication.

SSQ Head Office: 301 Elveden Road, Park Royal, London NW10 7SS

T: +44 (0) 20 8961 7725 F: +44 (0) 20 8965 7013

SSQ Northern Irish Office: 16A Crosshill Road, Crumlin, BT29 4BH

T: +44 (0) 75 9816 3622

SSQ Spanish Office: C/Academia Dequit No. 11° A, 32300 El Barco de Valdeorras, Orense, Spain

For any technical questions or guidance, please email directly technical@ssq.co.uk

E: info@ssq.co.uk W: www.ssqgroup.com

Coverage

Nail fixing method

Size (mm)	Lap (mm)								
	50	65	75	80	90	100	110	115	120
	Number of slates/m ²								
500 x 250	17.8	18.4	18.8	19.0	19.5	20.0	20.5	20.8	21.0

(NB: No allowance has been made for wastage*)

Hook fixing method

Size (mm)	Lap (mm)								
	50	65	75	80	90	100	110	115	120
	Number of slates/m ²								
500 x 250	17.8	18.4	18.8	19.0	19.5	20.0	20.5	20.8	21.0

(NB: No allowance has been made for wastage*)

* Please refer to the **SSQ Natural Roofing Slate Design and Fixing Guide** for full details (available on www.ssqgroup.com).



EXCLUSIVELY **NATURAL SLATE**