



Technical data

	Substance
Material	Stable aluminium pressure cylinder, ergonomic nylon handle

Application

For particularly quick and easy application of the AEROSANA VISCONN and AEROSANA VISCONN FIBRE sealants from 600ml foil cartridges onto smooth and rough mineral and non-mineral subsurfaces such as timber, wood fibreboards, OSB, stone, plaster, concrete etc.

For use with air compressors capable of up to 6.8bar, 300 l/min air flow.

Advantages

- ✓ Work more quickly: application and spreading of the sealant in a single working step
- ✓ Precise application of material: setting 1 for a line of sealant to close joints, setting 2 to spray over and seal surfaces
- ✓ Allows the technician to work with one hand
- ✓ No brush required
- ✓ Pressure: up to 6.8 bar (100 psi)



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Ecological Building Systems

For stockist information and full technical support for your project, please contact Ecological Building Systems or visit www.EcologicalBuildingSystems.com



Ireland: 046 9432104 Fax: 046 9432435 UK: 01228 711 511 Fax: 01228 712 280

info@EcologicalBuildingSystems.com