

Declaration of Performance No. DOP-03-FIRM-05-T2000 / Page 1 of 3

FIRMAHOLD Clipped Head Collated Nails



Material - Stainless Steel 304

Head Type - D-head

Nail Diameter (mm) - 2.8, 3.1

We hereby declare these designated products have performed initial type testing under system 3, Annex V of the regulation (EU) no. 305/2011 (Construction Products Regulation), with the reference to the harmonised European standard (hEN) BS EN 14592:2008+A1:2012 (Timber structures - Dowel type fasteners - Requirements) for screws intended for the use in "load bearing timber structures" and produced the calculation/test reports as attached;

The initial type testing has been carried out by independent notified body;
 BM Trada, NB # 2389, Chilton House, Stocking Lane, Hughenden Valley, High Wycombe, HP14 4ND


Certificate Number: CPR-J-00106-20 & CPR-J-00106-20

Test Report Number: 30-14691/1JP & 30-14150/JP

Factory Process Control (FPC) has been established by the factory.

This declaration is valid until there is a significant change in the product and declared characteristics. ie. raw material or change in production process.

This declaration is the responsibility of the importer ; T.I.Midwood & Co. Ltd.

Simon Midwood	Managing Director		TIMCO House 2013	2013
Name	Position	Signature	Location & Date	Test Year

Declaration of Performance No. DOP-03-FIRM-05-T2000 / Page 2 of 3

FIRMAHOLD Clipped Head Collated Nails D-head - Ring Shank - Ø2.8mm

Material & Geometry

Material	Stainless Steel 304
Screw diameter (mm)	2.8
Head area (mm ²)	26.55
Point length (mm)	4.02

Mechanical Strength & Stiffness

Characteristic yield moment $M_{y,k}$ at 45° [Nmm] in acc. to EN 409	2492
Characteristic withdrawal parameter (loading across the fibre) $f_{ax,k}$ [N/mm ²] in acc. to EN 1382 with density of wood $\rho_k = 350\text{kg/m}^3$	8.49
Characteristic withdrawal parameter (loading along the fibre) $f_{ax,k}$ [N/mm ²] in acc. to EN 1382 with density of wood $\rho_k = 350\text{kg/m}^3$	5.32
Characteristic head pull-through parameter $f_{tens,k}$ [N/mm ²] in acc. to EN 1383 with density of wood $\rho_k = 350\text{kg/m}^3$	23.95
Characteristic tensile capacity $f_{tens,k}$ [kN] in acc. to EN 1383	4.77

Durability

Coating (Finish)	N/A
Corrosion protection	Service Class 3 acc. to EN 1995-1-1

Declaration of Performance No. DOP-03-FIRM-05-T2000 / Page 3 of 3

FIRMAHOLD Clipped Head Collated Nails D-head - Ring Shank - Ø3.1mm

Material & Geometry

Material	Stainless Steel 304
Screw diameter (mm)	3.1
Head area (mm ²)	29.40
Point length (mm)	4.07

Mechanical Strength & Stiffness

Characteristic yield moment $M_{y,k}$ at 45° [Nmm] in acc. to EN 409	5432
Characteristic withdrawal parameter (loading across the fibre) $f_{ax,k}$ [N/mm ²] in acc. to EN 1382 with density of wood $\rho_k = 350\text{kg/m}^3$	8.26
Characteristic withdrawal parameter (loading along the fibre) $f_{ax,k}$ [N/mm ²] in acc. to EN 1382 with density of wood $\rho_k = 350\text{kg/m}^3$	5.13
Characteristic head pull-through parameter $f_{tens,k}$ [N/mm ²] in acc. to EN 1383 with density of wood $\rho_k = 350\text{kg/m}^3$	20.10
Characteristic tensile capacity $f_{tens,k}$ [kN] in acc. to EN 1383	5.70

Durability

Coating (Finish)	N/A
Corrosion protection	Service Class 3 acc. to EN 1995-1-1