



SAFETY DATA SHEET

Ref. CPT/9029.

PROMENADE TILES

PRODUCT AND COMPANY IDENTIFICATION

Product type:	Promenade tiles
Trade Name:	"Castile" Promenade Tiles
Manufacturer:	Castle Composites Limited Unit 1, Nisbet Way Ravenstruther Lanark, ML11 7SF
Phone No.:	01555 870003
Fax No.:	01555 870040

Technical Information

Reaction To Fire – A1 Non Combustible

Checkerplate Range

Length = 297mm, Width = 297mm, Depth = 12mm
Weight = 2.0kg per tile approx.
BS EN 1339 Pendulum Slip Test: 52 Wet (Low Potential For Slip)

Striated Range

Length = 297mm, Width = 297mm, Depth = 12mm
Weight = 2.0kg per tile approx.
BS EN 1339 Pendulum Slip Test: 58 Wet (Low Potential For Slip)

Riven Range

Length = 294mm, Width = 294mm, Depth = 14mm approx (due to surface texture)
Weight = 2.2kg per tile approx
BS EN 1339 Pendulum Slip Test: 42 Wet (Low Potential For Slip)

Diamond Cut

Length = 297mm, Width = 297mm, Depth = 12mm
Weight = 2.0kg per tile approx.

Imperial

Length = 297mm, Width = 297mm, Depth = 12mm
Weight = 2.0kg per tile approx.

COMPOSITION INFORMATION

Glass fibre reinforced concrete.

HAZARD IDENTIFICATION

Main hazards

The tiles as supplied are not classified as hazardous and as such do not present a risk to health or safety. Possibility of dust generation when cutting the tiles. Reference should be made to Health and Safety Data Sheets supplied by the manufacturers of adhesives or other materials used for fixing the tiles.

Health effects – Eyes

Dust from cutting will cause transient irritation by abrasion.

Health effects – Skin

Dust may cause irritation by abrasion.

Sharp edges on broken tiles may cause cuts and/or lacerations to skin.

Health effects – Inhalation

Exposure to dust may cause irritation of nose throat and respiratory tract.

FIRST AID MEASURES

First aid – Eyes

Immediately flood the eye with plenty of water holding the eye open. Obtain medical attention if soreness or redness persists.

First aid – Skin

Wash skin thoroughly with soap and water. Apply suitable dressings to cuts and abrasions. Obtain medical attention if cuts or abrasions are severe.

FIRE FIGHTING MEASURES

Product not combustible.

HANDLING AND STORAGE

Avoid breakages that might cause dust or sharp edges.

Stack on timber pallets and secure to pallet before moving.

If stacking pallets ensure ground is level and stack no more than two high.

PERSONAL PROTECTION

Wear protective gloves when handling tiles and suitable dust masks and eye protection when cutting tiles.