

SAFETY DATA SHEET

ASLON Rubber Acoustic / Protection Pads

PRODUCT AND COMPANY IDENTIFICATION

Product type: Rubber Pads

Trade Name: "Accoustic / Protection Aslon Rubber Pads"

Manufacturer: Castle Composites Limited

Units 1-5, Nisbet Way

Ravenstruther

Lanark, ML11 7SF

Phone No.: 01555 870003 Fax No.: 01555 870040

Packing Information

Shrink wrapped in packs, stacked on wooden pallets.

Product Information

Material Compound: recycled rubber bounded by PU binder

Dimensions: 100 x 100 mm / 150 x 150 mm / 200 x 200 mm

Thickness 10, 15 and 20 mm

Colour: Black

Color differences may occur, because of usage of recycled materials

Density: 730 kg/m3

Fire classification: Efl - EN 13501

Smoke classification: S2

Dimension Deviation: Width 2% and thickness 5%

Color Stability: Color may fade out with UV exposure and by using the tiles

Carbon black: Carbon black is a black dye that is used in every rubber tile. It can come

out due to weather influences.

Lime/Cement veil: Due to weather influences and by lime/cement veil of surrounding objects

a white rash can occur on the rubber layers.

Recycling: Products are 100 % recyclable.

Friction Coefficient: (According to VDI guideline

2700-14 en 15)

 $<0.7\mu$ at 10 mm