



850SERIES

TELESCOPIC SOFT CLOSE EXTENSION LADDER



TELESCOPIC SOFT CLOSE



Soft close mechanism to prevent finger trapping when closing the ladder

VARIOUS HEIGHTS TO SUIT THE JOB REQUIRED



Retracts to a compact size for easy transportation and storage



Lock indicators and automatic locking mechanism for added safety and security



Moulded foot brace provides maximum strength



850SERIES

TELESCOPIC SOFT CLOSE EXTENSION LADDER

150kg

MAX. LOAD

(Load includes user, tools, materials, etc.)



- Smaller folded sizes than standard extension ladders which makes the ladder easy to store, transport, and carry.
- Can be set to various heights for added convenience to suit the job required.
- Soft close design for smooth retraction to prevent finger trapping.

SPECIFICATIONS

Product Code	No. of Rungs	Closed Length	Extended Length	Safe Working Height*	Weight
85026	9	0.76m (2'6")	2.60m (8'6")	3.15m (10'4")	8.4kg
85029	10	0.79m (2'7")	2.90m (9'6")	3.42m (11'2")	9.4kg
85032**	11	0.82m (2'11")	3.23m (10'7")	3.95m (13')	12kg
85038**	13	0.88m (2'11")	3.80m (12'6")	4.55m (14'11")	14.8kg

*Based on 1.75m (5'9") as the average reach height of a person.

** Stabiliser supplied with these models.

Safety grip wall bumpers for firm grip and stability



Automatic locking mechanism for added security when in use

Lock indicators for increased safety



Single handed unlocking system for easy closure

Rubber hand grip provides a secure grip when carrying the ladder

Moulded foot brace provides maximum strength to protect against damage

Non-marking feet protect floor from damage

Wide stabiliser bar for added safety (85032 and 85038 models only)

Model 85032



EN131-6