

SOLID CONSERVATION

WHITE

APPLICABLE

- In public and residential buildings, where vintage looks from both inside and outside are required
- In heated, inhabited rooms
- In roof pitch range of 15°-90°
- Suitable on all common roofings with proper flashing

FEATURES

- Centre pivot wooden roof window
- Vintage design with black cladding elements and glazing bar
- Ventilation valve
- Toughened outer glass
- Elegant bottom handle
- Two passive ventilation positions via handle
- Double gasket system between frame and sash
- Double Low-e coating
- Easy installation
- 10 year guarantee

MATERIAL | WOOD AND FINISHING

- Kiln-dried laminated pine wood
- Timber from FSC certified forests
- Fungicide protection
- Water based lacquer

COVER PARTS

- Aluminium, powder coated, black (RAL 9005)

HANDLE

- Ergonomically designed moulded zinc handle, powder coated

HINGE

- Pivot hinge



CVY B911

PANE

Construction	4-16-4H
Thickness of glazing (mm)	24
Low E	■ ■
Gas	Argon
Toughened	■
U _g (W/m²K)	1.0
Total solar energy transmittance	0.55

WINDOW

U _w (W/m²K)	1.3
Water tightness	E1350
Air permeability	Class 4
Resistance to wind load	Class C4
Sound reduction	32 (-1;-5) dB

COLOUR

White painted	■
---------------	---

MEASURES

CODE	NOMINAL SIZE	FRAME EXTERNAL SIZE		PANE SIZE		VISIBLE GLASS		
		Width	Height	Width	Height	Width	Height	Effective Light Area m²
C2A	55x78	55	77,8	39,8	64,9	37,3	59	0,22
C4A	55x98	55	97,8	39,8	84,9	37,3	79	0,295
F6A	66x118	66	117,8	50,8	104,9	48,3	99	0,478
M4A	78x98	78	97,8	62,8	84,9	60,3	79	0,476
M6A	78x118	78	117,8	62,8	104,9	60,3	99	0,597
M8A	78x140	78	139,8	62,8	126,9	60,3	121	0,729

FLASHING RANGE FOR DIFFERENT ROOFING MATERIALS*



UNIVERSAL VINTAGE
Suitable for high profiled tiles and profiled materials between 16-120 mm



PLAIN TILE
For installation into plain tiles, max. overlapped thickness is 28 mm (2x14 mm), max. length is 340 mm. Suitable for a roof pitch range of 25° - 90°.



FLUSH FLASHING FOR SLATE
For 40 mm recessed installation into slates and flat roofing, up to 8 mm (max overall thickness is 16 mm)

* Combi solutions are also available, please contact your dealer for details.

BLIND RANGE*




BLACKOUT



ROLLER



AWNING



ROLLER SHUTTER

contrio.com

*For the right product code of blinds, please take the type of blind, size of RW and colour code, e.g. DUA C2A 4219