

TECHNICAL DATA SHEET GRANUFLEX 2019



## **D.I.Y. tiles**



Product pictures:	
Product description:	Rubber floor tile, developed for multiple purposes. Product contains SBR granulate (made from European tyres), temperature bonded with PU- binder. Upper side flat, profiled base.
Article number:	Diverse, depending on product. (product group D.I.Y. tiles, 221)
Dimensions:	400x400, 500x500mm. and 1000x1000mm. (25mm. thickness)
Size tolerance thickness:	+/- 8%
Size tolerance length-width:	+/- 1,5%
Weight:	16kg.m <sup>2</sup>
Weight tolerance:	-5% / +8% (5+3 because of the use of pigments)
Behaviour to fire:	Class E in accordance with EN13501-1, temperature allowance -40ºC / +80ºC
Thermal conductivity:	0,14 W.m <sup>2</sup> K
SVHC/ REACH:	Pass (concentrations: <0.1%). Granuflex © rubber tiles meet the requirements of the Reach regulation EU 1907/2006. Do not apply this product according to entry 50 Annex XVII of the Reach Regulation in situations where frequent skin or mouth contact is possible or as a surface on which children regularly play.
Product properties:	Water and frost resistant / suitable for indoor and outdoor use / tested on drop height (HIC) following standard EN1177:2008 / sound- and shock absorbing / anti-slip / 100% recyclable / 2 years warranty

