
Eaves comb filler

Designed to prevent entry of birds and vermin below profiled roof tiles





Use

- · At the eaves of a roof
- Below profiled roof tiles to exclude birds and vermin

Features and benefits

- Effective, quick and easy to fit
- Durable and totally resistant to decay
- Supplied in convenient 1m lengths

Quality

- Satisfies all NHBC requirements
- Manufactured to BS EN ISO 9001 and BS EN ISO 14001
- Complies with all relevant Building Regulations
- Meets all relevant British Standards

Material and colour choice

- Injection moulded in polypropylene
- Available in black only

Installation advice

- Fit on the top of the fascia board before tiles are laid. The comb must angle outwards away from the roof
- Secure with clout nails through the holes provided
- Bed bottom row of tiles on to the comb

How to order

• Measure the overall length of the eaves and divide by 1m to determine the number of combs required

Bill of quantity

NSSPlus

G20 Carpentry/Timber Framing/First Fixing

900° EAVES SOFFIT VENTILATORS

• Manufacturer: Timloc Building Products, Rawcliffe Road, Goole, East Yorkshire, DN14 6UQ. Tel: 01405 765567,

Fax: 01405 720479. Web: www.timloc.co.uk

- Product Reference: 1136
- Type: Eaves Comb Filler (1000mm)
- Colour: Black

Product code

6m eaves vent pack

Depth of comb	Length	Product code
55mm	1m	1136