# Roll form eaves vent roll out rafter tray

Easy to install system to maintain ventilation between insulation and roofing felt



#### Use

- For pitched roof eaves ventilation
- On standard pitched roofs where the pitch is 15 degrees or more and the roof void is an attic or loft space
- On roofs with rafter spacings of between 400mm and 600mm centres

# **Features and benefits**

- Durable, totally resistant to decay, easy to fit
- Supplied in convenient 6m rolls
- Suitable for new build and refurbishment projects

#### Quality

- Satisfies all NHBC requirements
- Manufactured to BS EN ISO 9001 and BS EN ISO 14001
- Complies with all relevant Building Regulations
- Meets all relevant British Standards

## **Material and colour choice**

- Manufactured by vacuum forming in UPVC
- Available in black only

# **Products in the system**

Product 1121 - 300mm Roll form eaves vent

Single row of 300mm roll panel coverage suitable for:			
Insulation depth	Min roof pitch (deg)		
225mm	40°		
250mm	45°		

#### Product 1131 - 600mm Roll form eaves vent

Single row of 600mm roll panel coverage suitable for: Insulation depth Min roof pitch (deg)		
225mm	20°	
250mm	22.5°	
300mm	27.5°	
400mm	37.5°	

### Product 1151 - 800mm Roll form eaves vent

Single row of 800mm roll panel coverage suitable for:			
Insulation depth	Min roof pitch (deg)		
225mm	17.5°		
250mm	20°		
300mm	22.5°		
400mm	30°		



#### Installation advice

- Unroll the ventilator along the rafters along the full length of the eaves and along both sides of the building to create a cross flow ventilation action
- Position centrally above the wall plate. This is the narrowest part of the roof where the roof insulation is most likely to constrict the airflow
- Push the corrugations down over the top of the rafters and secure using clout nails or staples

#### How to order

• Measure the overall length of the eaves to be ventilated and divide by 6m to determine the number of rolls of ventilator required

## **Product code**

Roll form eaves vent				
Depth of ventilation channel	Width	Length	Product code	
> 25mm	300mm	6m	1121	
> 25mm	600mm	6m	1131	
> 25mm	800mm	6m	1151	

**NS**SPlus

