



Olympic Fixing Products Ltd
 Unit 1-4, Venture Court, Metcalf Drive
 Altham, Accrington, Lancashire
 BB5 5WH Tel:01282-778923
 Email:accrington@olympicfixings.co.uk
 www.olympicfixings.com

TWEED

Terry brushed acrylic liner coated in smooth latex, fully dipped & sandy finished latex, thumb fully dipped

EN 420:2003+A1:2009 – Protective gloves. General requirements.
 EN 388:2016 – Protective gloves against mechanical risks.
 EN 511:2006- Protective gloves from cold

SIZE: 7,8,9,10

EN 388:2016



A B C D E
 2 1 3 1 X

EN 511:2006



A B C
 0 1 1



APPROVED BY :

SATRA Technology
 Centre, Wyndham Way,
 Telford Way, Kettering
 Northamptonshire,
 NN16 8SD, United Kingdom
**Nº Certificado: Number
 8525 Issue2**

EN 388:2016

PROTECTION LEVELS

	1	2	3	4	5
A) Resistance to Abrasion	100	500	2000	8000	-----
B) Blade Cut Resistance	1,2	2,5	5,0	10,0	20,0
C) Tear Resistance	10	25	50	75	-----
D) Puncture resistance	20	60	100	150	-----
E)TDM Cut Resistance	Not Applicable				

EN 511:2006

PROTECTION LEVELS

	0	1	2	3	4
A) Resistance to Convective Cold	Not passed	$0.1 \leq I_{TR} < 0.15$	$0.15 \leq I_{TR} < 0.22$	$0.22 \leq I_{TR} < 0.30$	$0.30 \leq I_{TR}$
B) Resistance to Contact Cold	Not passed	$0.025 \leq R < 0.05$	$0.050 \leq R < 0.10$	$0.100 \leq R < 0.15$	$0.150 \leq R$
C) Permeability of Water	Not passed	No water penetration			

USE

Building, construction, waste collection, wood industry, agriculture, maintenance and general purpose. Excellent grip dry and wet.

NOT RECOMMENDED FOR

Never use them when there is a risk of trapping by mobile machines parts.

CLEANING AND MAINTENANCE

Both new and used gloves should be thoroughly inspected, especially after cleaning treatment, before being worn to ensure no damage is present.
 Gloves should not be left in contaminated condition if re-use is intended in which case gloves should be cleaned as far as possible, provided no serious hazard exists, before removal from hands.

STORAGE

Ideally stored at in dry conditions in the original package, sheltered from direct light.

OBSOLESCENCE

When stored as recommended will not suffer change in mechanical properties from date of manufacture. Service life cannot be specified and depends on application and responsibility of user to ascertain suitability of the glove for its intended use.

GENERAL INFORMATION

These products are manufactured under a Quality System, which has been registered and meets the requirements of ISO 9001: 2000. None of the raw materials or processes used in the manufacture of these products is known to have any harmful effect on the wearer.

NOTE

The information contained herein is intended to assist the wearer in selection of Personal Protective Equipment. The results of physical and where appropriate chemical tests should also help in glove selection, however it is the responsibility of the user not the manufacturer to determine the glove suitability for the intended use.