

## VELUX flat glass rooflight




### Roof pitch



Special consideration for applications below roof pitch 5°:

If installed below 5°, there is an increased risk of water, dirt and debris standing on the glass, which in some cases, can cause slight discoloration of the glass over time. Installation of flat glass below 5° does not affect the lifetime and quality of the product compared to installation at 5°.



VELUX flat glass rooflights are a stylish addition to our flat roof window range featuring an attractive eye-catching glass pane.

### Convenience and high performance

As well as an innovative design, the flat glass rooflight features all of the outstanding specifications you'd expect from VELUX.

- It comprises a maintenance-free PVC framework and lacquered aluminium cladding.
- Highly energy efficient, our high-performance insulation is integrated into the frame to give the best possible protection against heat loss.



### Fixed rooflight

The VELUX fixed flat glass rooflight can transform any space and is ideal where there is a need for bringing in daylight without ventilation. The double glazed unit has a laminated inner pane for additional safety.




### Electrically operated rooflight

The VELUX vented flat glass rooflight provides ventilation and fresh air through the roof, and it can be operated automatically with the VELUX INTEGRA® wall switch.

## VELUX curved and flat glass rooflight

### Options and pricing

#### Roof pitch



Make your electric roof windows smart

Find out more on page 26 or at [velux.co.uk/active](http://velux.co.uk/active)

#### U-VALUES

Combining a **curved glass top cover** with either an electrically operated base unit or a fixed base unit will give you a value of 0.72 Urc, ref300.


Combining a **flat glass top cover** with either an electrically operated base unit or a fixed base unit will give you a value of 0.79 Urc, ref300.

### 1. CHOOSE YOUR TOP COVER

CurveTech



or




CURVED GLASS (ISD 1093)

- Curved glazing and glass-to-edge design ensure uninterrupted drainage.
- Curved shape ensures a clearer view to the sky.
- Up to 6mm scratch-free glazing.
- Installation in 0-15° roof pitch.
- Recommended option for visible installations.


FLAT GLASS (ISD 2093)

- Flat glass design fits the roof line.
- 4mm scratch-free glazing.
- Installation in 2-15° roof pitch.

### 2. NOW CHOOSE A BASE UNIT



or



ELECTRICALLY OPERATED BASE UNIT (CVP)

- High-insulated PVC sash construction.
- 2-layer low-energy pane.
- Laminated pane on the inside.
- Openable construction.
- VELUX INTEGRA® convenient operation.
- Integrated rain sensor for automatic closing during rain.

FIXED BASE UNIT (CFP)

- High-insulated PVC sash construction.
- 2-layer low-energy pane.
- Laminated pane on the inside.

### Curved and flat glass rooflight

External frame size including kerb (nominal w x h) cm  
Structural openings (nominal w x h) cm

Code	Description	060060	060090	080080	090090	100100	090120	120120	100150
CHOOSE A TOP COVER									
ISD 1093	Curved glass top cover.	£392	£420	£442	£508	£552	£585	£718	£729
ISD 2093	Flat glass top cover.	£306	£328	£345	£397	£431	£457	£561	£569
NOW CHOOSE A BASE, EITHER FIXED OR VELUX INTEGRA®									
Fixed									
CFP 0073QV	Fixed flat roof window base with double glazed insulating glass unit featuring laminated inner pane for safety.	£283	£302	£318	£366	£398	£422	£486	£509
VELUX INTEGRA®									
CVP 0673QV	Electrically operated flat roof window base with double glazed insulating glass unit featuring laminated inner pane for safety.	£683	£702	£718	£766	£798	£822	£886	£909
Accessories									
ZCE 0015	Extension kerb 150mm (for warm roof installations only).	£150	£157	£161	£177	£192	£196	£217	£219
ZZZ 210	Frame fixing kit for roof material.	£34	£36	£37	£41	£44	£45	£50	£50

- ▶ All roof windows have a delivery time of 2 days.
- ▶ Delivery time is in working days from receipt of orders placed before 4pm (UK) and 11.30am (NI).