



LOFT LADDER RANGE



DISCOVER A LOFT SOLUTION TO SUIT YOUR NEEDS

ACCESS SOLUTIONS

Werner loft ladders come in a variety of sizes and provide different solutions. From space-saving and compact designs to lightweight aluminium and timber loft ladders, we have the full range of loft ladders to suit your requirements.



Budget



Space-saving



Insulated



Quick
Installation



Fire
Resistant



Handrail

INSTALL WITH EASE

Each Werner loft ladder comes with a comprehensive instruction manual that guides you through the step-by-step installation process. Our collection of easy-to-follow videos will also aid you in the installation of your loft ladder.

When considering our loft ladders with insulated trapdoors, you need to pay attention to the U-value. This is a measure of how much heat is lost through the loft hatch. The better insulated, the lower the U-value will be.



GUARANTEE

Manufactured and tested to the highest standard, all Werner loft ladders are equipped with safety-enhancing features to help you access your loft safely. Our 5-year guarantee applies across all Werner loft ladders.



Our guarantee includes faults arising from defects in workmanship or materials except for:


- Ordinary wear and tear of the product.
- Damage caused by misuse or abuse of the product.
- Damage caused by failure to comply with all written warnings and instructions for the product.
- Damage caused by an attempted repair of the product.

Material - means a material or component used by Werner in the manufacture of the product.


Workmanship - means the handling, assembly and manufacturing processes performed by or on behalf of Werner in order to manufacture the product.

GUIDE TO BUYING THE

Height




Measure the floor to loft floor height: the vertical distance from floor to loft floor.



For timber loft ladders, you will need to measure from the finished floor to the finished ceiling.

Hatch Opening Size




Measure the rough openings in your ceiling, both width and length. The common UK hatch size is approximately 562mm x 726mm (22" x 29").


Max. Height Required	Any Restrictions?	Your Ladder Options
Below 2m	Small Hatch Openings	Stowaway®   
	Limited Loft Space	Easi-build®    Eco S-Line   
	One Person Assembly	Easi-build®    Stowaway®   
2m - 3m	Small Hatch Openings	Deluxe   Easiway     Easy Stow    
	Limited Loft Space	Easi-build®    Eco S-Line    FireguardPRO™   
	One Person Assembly	Deluxe   Easi-build®    Easiway    
Over 3m with extension kit*	Limited Loft Space	Easi-build®    Eco S-Line   
	One Person Assembly	Easi-build®   

RIGHT LOFT LADDER

Loft Space



Some loft ladders are stored within the trapdoor so no floor space is used. You will need to measure the **opening arc** to ensure there is space to swing out the ladder sections.



Other ladders require additional storage space in the loft. You should measure the **clearance arc** and **length behind the hatch** in the loft; you must have adequate space for storage. See the '**limited loft space**' option overleaf if this space is restricted.

FireguardPRO™

Stowaway®

Spacemaker

Standard Aluminium

Stowaway®

Telescopic

Easy Stow

Spacemaker

Standard Aluminium

FireguardPRO™

ThermoPLUS™

Timberline

ThermoPLUS™

Stowaway®

Telescopic

ThermoPLUS™

Timberline

Stowaway®

Telescopic

Timberline

 Timber

 Aluminium

 Budget

 Space-saving

 Insulated

 Quick Installation

 Fire Resistant

 Handrail

*Timber extension kit available separately.

STANDARD LOFT LADDERS

2 and 3 Section Aluminium Loft Ladders



QUICK INSTALLATION

LIGHTWEIGHT AND EASY INSTALLATION

Suitable for floor to loft floor heights up to 3m (9'10")

- ① Includes handrail for added safety
- ② Slip-resistant D-shaped rungs for comfort and security
- ③ Locking catches for added safety
- ④ Slip-resistant feet for added grip

Product includes:

Ladder, stowing pole, and handrail



Max. Load
(Load includes user, tools, materials, etc.)



EN14975



WATCH THE VIDEO



Floor Thickness	Min. Loft Opening Length	
	2 Section	3 Section
7.6cm (3")	0.49m (1'7")	0.40m (1'4")
10.2cm (4")	0.50m (1'8")	0.41m (1'4")
12.7cm (5")	0.51m (1'8")	0.43m (1'5")
15.3cm (6")	0.53m (1'9")	0.44m (1'5")
17.8cm (7")	0.54m (1'9")	0.45m (1'6")
20.3cm (8")	0.55m (1'9")	0.46m (1'6")

SPECIFICATIONS

Product Code	Sections	Max. Floor to Loft Floor Height	Min. Floor to Loft Floor Height	Min. Loft Opening Width	Min. Clearance Arc	Min. Storage Space	Product Weight
76002	2	2.69m (8'10")	2.13m (6'10")	0.38m (1'3")	0.71m (2'4")	1.27m (4'2")	4.3kg
76003	3	3.00m (9'10")	2.13m (6'10")	0.38m (1'3")	0.71m (2'4")	1.12m (3'8")	5.1kg

EASIWAY

Aluminium Loft Ladder



ULTRA COMPACT

SMOOTH GLIDING OPERATION

Suitable for floor to loft floor heights up to 3m (9'10")

- 1 Compact lightweight design - requires less storage space in the loft
- 2 Pivot arm for smooth gliding operation when lowering or stowing the ladder
- 3 Unique shoot bolt mechanism to lock ladder in place when in use
- 4 Handrail for comfort and safety while climbing
- 5 Easy to use and smooth to glide when lowering or stowing the ladder
- 6 Wide and comfortable treads for comfort when climbing
- 7 Slip-resistant feet for added grip

Product includes:

Ladder, stowing pole, and handrail



WATCH THE VIDEO



SPECIFICATIONS

Product Code	Max. Floor to Loft Floor Height	Min. Floor to Loft Floor Height	Min. Loft Opening Size (LxW)	Min. Clearance Arc	Min. Storage Space	Product Weight
31334000	3.00m (9'10")	2.30m (7'7")	0.51m x 0.43m (1'8" x 1'5")	0.75m (2'6")	1.05m (3'5")	7.0kg



Max. Load
(Load includes user, tools, materials, etc.)



EN14975

SPACEMAKER

Aluminium Loft Ladder



ULTRA COMPACT

DESIGNED FOR NARROW LOFT HATCHES

Suitable for floor to loft floor heights
up to 2.6m (8'6")

- 1 Lightweight but sturdy 2 section sliding design, complete with all fittings
- 2 Wide, slip-resistant rungs for comfort when climbing
- 3 Unique shoot bolt mechanism to lock ladder in place when in use
- 4 Easy to use when lowering and stowing the ladder
- 5 Slip-resistant feet for added grip

Product includes:

Ladder and stowing pole



WATCH THE VIDEO



SPECIFICATIONS

Product Code	Max. Floor to Loft Floor Height	Min. Loft Opening Size (LxW)	Min. Clearance Arc	Min. Storage Space	Product Weight
30234000	2.60m (8'6")	0.46m x 0.41m (1'6" x 1'4")	0.86m (2'10")	1.22m (4')	5.0kg



Max. Load
(Load includes user,
tools, materials, etc.)



EN14975

EASY STOW

Aluminium Loft Ladder



SAFE LOFT ACCESS SOLUTION

SPRING-ASSISTED OPENING AND CLOSING

Suitable for floor to loft floor heights up to 3m (9'10")

- 1 Extended in-loft handrail for added safety when entering or leaving the loft
- 2 Slip-resistant D-shaped rungs for comfort and security while climbing
- 3 Locking catches for added safety
- 4 Slip-resistant feet for added stability
- 5 Spring-assisted Easy Stow system gives total control when lowering or stowing the loft ladder

Product includes:

Ladder, stowing pole, handrail, and spring-assisted stowage



WATCH THE VIDEO



Max. Load
(Load includes user,
tools, materials, etc.)



EN14975

Floor Thickness	Min. Loft Opening Length
7.6cm (3")	0.40m (1'4")
10.2cm (4")	0.41m (1'4")
12.7cm (5")	0.43m (1'5")
15.3cm (6")	0.44m (1'5")
17.8cm (7")	0.45m (1'6")
20.3cm (8")	0.46m (1'6")

SPECIFICATIONS

Product Code	Max. Floor to Loft Floor Height	Min. Floor to Loft Floor Height	Min. Loft Opening Width	Min. Clearance Arc	Min. Storage Space	Product Weight
76013	3.00m (9'10")	2.13m (6'10")	0.38m (1'3")	0.71m (2'4")	1.12m (3'8")	6.7kg

DELUXE

Aluminium Loft Ladder



SAFE LOFT ACCESS SOLUTION

UNPARALLELED DURABILITY AND RESILIENCE FOR HEAVY-DUTY USE

Suitable for floor to loft floor heights up to 3.25m (10'8")

- 1 Spring-assisted pivot arm for smooth gliding when lowering or stowing the ladder
- 2 Twin handrails for secure climbing
- 3 Ladder attaches to loft hatch for easier deployment
- 4 Deep and slip-resistant steps for comfort and security
- 5 Sturdy and heavy-duty 2 section sliding design made from heavy-duty aluminium
- 6 Slip-resistant feet for added grip

Product includes:

Ladder, stowing pole, handrails, and spring-assisted stowage



WATCH THE VIDEO



Max. Load
(Load includes user,
tools, materials, etc.)



SPECIFICATIONS

Product Code	Max. Floor to Loft Floor Height	Min. Floor to Loft Floor Height	Min. Loft Opening size (LxW)	Min. Clearance Arc	Min. Storage Space	Product Weight
30634000	3.25m (10'8")	2.31m (7'7")	0.69m x 0.51m (2'3" x 1'8")	1.03m (3'5")	1.60m (5'3")	18.4kg

TELESCOPIC

Aluminium Loft Ladder



ULTRA COMPACT

IDEAL FOR SMALL CONFINED LOFT SPACES

Suitable for floor to loft floor heights up to 2.88m (9'5")

- 1 Compact design for small hatches with minimal storage space
- 2 Heavy-duty spring system enables easy deployment and closure
- 3 Automatic locking and release for convenience and safety
- 4 Manufactured in anodised aluminium for durability and scratch-resistance
- 5 Telescopic design for easy adjustment to 3 different heights
- 6 Extra-wide steps for comfort and safety
- 7 Slip-resistant rubber feet for added grip and protects floor from damage



Product includes:

Ladder, stowing pole, and spring system



WATCH THE VIDEO



SPECIFICATIONS

Product Code	Max. Floor to Loft Floor Height	Min. Floor to Loft Floor Height	Min. Loft Opening Size (LxW)	Min. Clearance Arc	Min. Storage Space	Product Weight
30100000	2.61m (8'7")	2.17m (7'1")	0.60m x 0.51m (2' x 1'8")	0.24m (9")	0.24m (9")	12.0kg
30100100	2.88m (9'5")	2.43m (8')	0.60m x 0.51m (2' x 1'8")	0.24m (9")	0.24m (9")	13.0kg



Max. Load
(Load includes user,
tools, materials, etc.)



Safety Tested

TIMBERLINE

Complete Timber Loft Access Kit

SIMPLE LOFT ACCESS SOLUTION

Suitable for floor to ceiling heights up to 2.85m (9'4")

- 1 Uses no further loft floor space – ladder stores compactly within trapdoor
- 2 Spring-assisted stowage for smooth opening and closing
- 3 26mm insulated trapdoor and rubber draught excluder prevents loss of heat and draughts
- 4 Hinge clip prevents the sections from folding for added safety
- 5 Slip-resistant treads for comfortable climbing
- 6 Slip-resistant feet for added stability

Complete loft solution includes:

Ladder, stowing pole, loft surround, hinge clip, 26mm insulated trapdoor, and spring-assisted stowage



WATCH THE VIDEO



SPECIFICATIONS

Product Code	Max. Floor to Ceiling Height	Min. Loft Opening Size (LxW)	Opening Arc	Sections x Treads	Trapdoor Insulation	Product Weight
34530300	2.85m (9'4")	1.15m x 0.57m (3'9" x 1'10")	1.61m (5'3")	3 x 4	26mm (UV 1.3)	18.0kg
34635000*	Timber Extension Kit (extends floor to ceiling height to 3.32m (10'10"))					

*Timber extension kit available separately



Max. Load
(Load includes user,
tools, materials, etc.)



EN14975



EN12207-4
Airtight

ECO S-LINE

Complete Timber Loft Access Kit



SAFE LOFT ACCESS SOLUTION

SAFE LOFT ACCESS SOLUTION

Suitable for floor to ceiling heights up to 2.86m (9'5")

- 1 Spring-assisted stowage for smooth opening and closing
- 2 Handrail to aid safe climbing, can be fitted on either side
- 3 Uses no further loft floor space - ladder stores within trapdoor
- 4 26mm insulated trapdoor and rubber draught excluder prevents loss of heat and draughts
- 5 Hinge clip prevents the sections from folding for added safety
- 6 Slip-resistant treads for comfortable climbing
- 7 Slip-resistant feet for added stability



Complete loft solution includes:

Ladder, handrail, stowing pole, loft surround, hinge clip, 26mm insulated trapdoor, and spring-assisted stowage



WATCH THE VIDEO



SPECIFICATIONS

Product Code	Max. Floor to Ceiling Height	Min. Loft Opening Size (LxW)	Opening Arc	Sections x Treads	Trapdoor Insulation	Product Weight
34535000	2.86m (9'5")	1.15 x 0.57m (3'9" x 1'10")	1.62m (5'4")	3 x 4	26mm (UV 1.3)	20.7kg
34635000*	Timber Extension Kit (extends floor to ceiling height to 3.33m (10'11"))					

*Timber extension kit available separately



Max. Load
(Load includes user,
tools, materials, etc.)



EN14975



EN12207-4

Airtight

STOWAWAY[®]

Complete Timber Loft Access Kit



ULTRA COMPACT

IDEAL FOR TIGHT SPACES

Suitable for floor to ceiling heights up to 2.84m (9'4")

- 1 Ultra-compact – ideal for tight/ small hatch openings
- 2 Compact design fits securely into small hatches without joist alterations
- 3 Spring-assisted stowage for smooth opening and closing
- 4 36mm insulated trapdoor and rubber draught excluder prevents loss of heat and draughts
- 5 Slip-resistant treads for comfortable climbing
- 6 Slip-resistant feet for added stability



Complete loft solution includes:

Ladder, stowing pole, loft surround, 36mm insulated trapdoor, and spring-assisted stowage



WATCH THE VIDEO



Max. Load
(Load includes user,
tools, materials, etc.)



EN14975



EN12207-4
Airtight

SPECIFICATIONS

Product Code	Max. Floor to Ceiling Height	Min. Loft Opening Size (LxW)	Opening Arc	Sections x Treads	Trapdoor Insulation	Product Weight
34536000	2.84m (9'4")	0.93m x 0.60m (3'1" x 2')	1.14m (3'9")	4 x 3	36mm (UV 0.96)	18.3kg

EASI-BUILD®

Complete Timber Loft Access Kit



QUICK INSTALLATION

QUICK AND EASY INSTALLATION

Suitable for floor to ceiling heights up to 2.75m (9')

- 1 Click-fix technology reduces installation time by up to 30 minutes compared to other timber loft access kits
- 2 Ladder folds and is stored onto the trapdoor to maximise loft space
- 3 Spring-assisted stowage for smooth opening and closing
- 4 56mm insulated trapdoor and rubber draught excluder prevents loss of heat and draughts
- 5 Slip-resistant treads for comfortable climbing
- 6 Slip-resistant feet for added stability



Complete loft solution includes:

Ladder, stowing pole, loft surround, 56mm insulated trapdoor, and spring-assisted stowage



WATCH THE VIDEO



SPECIFICATIONS

Product Code	Max. Floor to Ceiling Height	Min. Loft Opening Size (LxW)	Opening Arc	Sections x Treads	Trapdoor Insulation	Product Weight
34538000	2.75m (9')	1.15m x 0.56m (3'9" x 1'10")	1.49m (4'11")	3 x 4	56mm (UV 0.62)	17.9kg
34638000*	Timber Extension Kit (extends floor to ceiling height to 3.22m (10'7"))					

*Timber extension kit available separately



Max. Load
(Load includes user, tools, materials, etc.)



EN14975



EN12207-4
Airtight

THERMOPLUS™

Complete Timber Loft Access Kit



ULTRA ENERGY-EFFICIENT

ULTRA ENERGY-EFFICIENT

Suitable for floor to ceiling heights up to 2.86m (9'5")

- ① 64mm insulated trapdoor and rubber draught excluder prevents loss of heat and draughts
- ② Spring-assisted stowage for smooth opening and closing
- ③ Heavy-duty handrail that can be positioned on either side for added safety when climbing into the loft
- ④ Ladder folds and is stored onto the trapdoor to maximise loft space
- ⑤ Hinge clip prevents the sections from folding for added safety
- ⑥ Slip-resistant treads for comfortable climbing
- ⑦ Slip-resistant feet for added stability



Complete loft solution includes:

Ladder, handrail, stowing pole, loft surround, hinge clip, 64mm insulated trapdoor, and spring-assisted stowage



WATCH THE VIDEO



SPECIFICATIONS

Product Code	Max. Floor to Ceiling Height	Min. Loft Opening Size (LxW)	Opening Arc	Sections x Treads	Trapdoor Insulation	Product Weight
34537000	2.86m (9'5")	1.15m x 0.57m (3'9" x 1'10")	1.62m (5'4")	3 x 4	64mm (UV 0.48)	25.3kg
34635000*	Timber Extension Kit (extends floor to ceiling height to 3.33m (10'11"))					

*Timber extension kit available separately



Max. Load
(Load includes user, tools, materials, etc.)



EN14975



EN12207-4
Airtight

FIREGUARD^{PRO}™

Complete Timber Loft Access Kit



FIRE RESISTANT

FIRE RESISTANT

Suitable for floor to ceiling heights up to 2.88m (9'5")

- 1 Best-in-Class fire-resistant trapdoor to restrict the spread of flames between different levels of the building
- 2 Spring-assisted stowage for smooth opening and closing
- 3 Ladder folds and is stored onto the trapdoor to maximise loft space
- 4 56mm insulated trapdoor and rubber draught prevents loss of heat and draughts
- 5 Slip-resistant treads for comfortable climbing
- 6 Slip-resistant feet for added stability



Complete loft solution includes:

Ladder, stowing pole, loft surround, architrave strips, 56mm insulated trapdoor, and spring-assisted stowage



▶ WATCH THE VIDEO



Max. Load
(Load includes user, tools, materials, etc.)



EN14975



EN12207-4
Airtight



EN13501-2
Fire Resistance Tested

SPECIFICATIONS

Product Code	Max. Floor to Ceiling Height	Min. Loft Opening Size (LxW)	Opening Arc	Sections x Treads	Trapdoor Insulation	Product Weight
34539000	2.88m (9'5")	1.15m x 0.56m (3'9" x 1'10")	1.60m (5'3")	3 x 4	56mm (UV 0.7)	33.2kg
34639000*	Timber Extension Kit (extends floor to ceiling height to 3.35m (11'))					

*Timber extension kit available separately

WERNER LOFT LADDER RANGE AT A GLANCE

Code	76002	76003	31334000	30234000	76013	30634000	30100000	30100100	34530300	34535000	34536000	34538000	34537000	34539000
Description	2 Section Loft Ladder	3 Section Loft Ladder	Eastway	Spacemaker	Easy Slow	Deluxe	Telescopic 2.6m	Telescopic 2.9m	Timberline	Eco S-Line	Stowaway®	Easi-build®	ThermoPLUS™	FriguardPRO™
Material	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium	Timber	Timber	Timber	Timber	Timber	Timber
Max. Floor to Loft Floor Height	2.69m (8'10")	3.00m (9'10")	3.00m (9'10")	2.60m (8'6")	3.00m (9'10")	3.25m (10'8")	2.61m (8'7")	2.88m (9'5")	-	-	-	-	-	-
Min. Floor to Loft Floor Height	2.13m (6'10")	2.13m (6'10")	2.30m (7'7")	1.45m (4'9")	2.13m (6'10")	2.31 (7'7")	2.17m (7'1")	2.43m (8')	-	-	-	-	-	-
Max. Floor to Ceiling Height (m)	-	-	-	-	-	-	-	-	2.85m (9'4")	2.86m (9'5")	2.84m (9'4")	2.75m (9')	2.86m (9'5")	2.88m (9'5")
Min. Loft Opening Size (LxW)	0.46m - 0.55m* x 0.38m (1'7" - 1'9" x 1'3")	0.40m - 0.46m* x 0.38m (1'4" - 1'6" x 1'3")	0.51m x 0.43m (1'8" x 1'5")	0.46m x 0.41m (1'6" x 1'4")	0.40m - 0.46m* x 0.38m (1'4" - 1'6" x 1'3")	0.69m x 0.51m (2'3" x 1'8")	0.60m x 0.51m (2' x 1'8")	1.15m x 0.57m (3'9" x 1'10")	1.15m x 0.57m (3'9" x 1'10")	1.15 x 0.57m (3'9" x 1'10")	0.93m x 0.60m (3'1" x 2')	1.15 x 0.56m (3'9" x 1'10")	1.15m x 0.57m (3'9" x 1'10")	1.15m x 0.56m (3'9" x 1'10")
Trapdoor Insulation	-	-	-	-	-	-	-	26mm (UV 1.3)	26mm (UV 1.3)	26mm (UV 1.3)	36mm (UV 0.96)	56mm (UV 0.62)	64mm (UV 0.48)	56mm (UV 0.7)
Min. Clearance Arc	0.71m (2'4")	0.71m (2'4")	0.75m (2'6")	0.86m (2'10")	0.71m (2'4")	1.03m (3'5")	0.24m (9")	0.24m (9")	-	-	-	-	-	-
Min. Storage Space in Loft	1.27m (4'2")	1.12m (3'8")	1.05m (3'5")	1.22m (4')	1.12m (3'8")	1.60m (5'3")	0.24m (9")	0.24m (9")	-	-	-	-	-	-
Opening Arc	-	-	-	-	-	-	-	1.61m (5'3")	1.62m (5'4")	1.62m (5'4")	1.14m (3'9")	1.49m (4'11")	1.62m (5'4")	1.60m (5'3")
Steps	10	12	12	10	12	14	9	10	12	12	12	12	12	12
Sections	2	3	3	2	3	2	1	1	3	3	4	3	3	3
Handrail	✓	✓	✓	✗	✓	✓	✗	✗	✗	✓	✗	✗	✓	✗
Architrave	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✓
Extension Kit	✗	✗	✗	✗	✗	✗	✗	✓	✓	✓	✗	✓	✓	✓
Standard	EN14975	EN14975	EN14975	EN14975	EN14975	EN14975	Safety Tested	Safety Tested	EN14975 EN12207-4	EN14975 EN12207-4	EN14975 EN12207-4	EN14975 EN12207-4	EN14975 EN12207-4	EN14975 EN12207-4 EN13501-2
Product Weight	4.3kg	5.1kg	7.0kg	5.0kg	6.7kg	18.4kg	12.0kg	13.0kg	18.0kg	20.7kg	18.3kg	17.9kg	25.3kg	33.2kg

*Minimum floor opening length depends on the floor thickness. For more information see page 9 for Easy Slow Loft Ladder (76013) and page 6 for 2 and 3 section loft ladders (76002 and 76003).



SEE FULL
LOFT RANGE



wernerco.co.uk

Werner UK Sales and Distribution Limited
Blackwater Trading Estate, The Causeway,
Maldon, Essex, CM9 4LJ.